

Product: GDM2106-A0U-10F ☑





GDM Standard DIN Standard Field Attachable Connector: Form A, 3-pin (2+1PE; PE across cable outlet), black housing, screw type, M16; without circuitry, 230 V AC/DC, 16 A


Product Description


GDM Standard DIN Standard Field Attachable Connector: Form A, 3-pin (2+1PE; PE across cable outlet), black housing, screw type, M16; without circuitry, 230 V AC/DC, 16 A


Technical Drawing














Technical Specifications

Technical Data

Product Family:	Valve Connectors	
Product Sub Family:	GDM Standard	
Brand:	Hirschmann	
Connector Type:	Field attachable	
Type of Contact / Gender:	Female	
Connector Design:	Angled	
Number of Pins:	2+PE (PE across cable outlet)	
Coding:	A	
Shielding:	Unshielded	
Attachment Type:	Central Screw	
Replacement for:	ID: 934393100 Name: GDM 2016 schwarz	
Rated Impulse Voltage:	4.0 kV	
Operating Voltage:	230 V AC/DC	
Rated Current*:	16 A	
Contact Resistance:	≤ 10 mOhm	
Insulation Resistance:	> 10^9 Ohm	
Mating Cycles:	≤ 50	
Type of Connection:	Screw	
Cable Gland:	M16	
Conductor Cross Section:	0.25 - 1.5 mm ²	
Suitable Cables:	Ø 4.5 - 10 mm	
Ambient Temperature (Operation)*:	-40 °C - +125 °C	
Protection Degree / IP Rating**:	IP65	
Design Standard:	DIN EN 175301-803-A, ISO 4400	
Pollution Degree:	3 acc. to DIN EN 60664-1 (VDE 0110-1)	
Clearance / Creepage Distance:	nce: DIN EN 60664-1 (2008/01); VDE 0110-1	
Overvoltage Category: III acc. to DIN EN 60664-1 (VDE 0110-1)		

Materials

Contact Base Material:	CuZn			
Contact Plating:	Cu/Sn			
Contact Bearer Material:	PA GF			
Contact Bearer Color:	black			
Flammability Class (Contact Bearer):	UL 94 HB			
Housing Material:	PA GF			
Housing Color:	Black			
Flammability Class (Housing):	UL 94 HB			
Cable Gland Material:	PA GF			
Cable Gland Gasket:				
Cable Gland Color:				
Attachment Material:	Steel, Philips combi slot			
Gasket Material:	Sold separately			

Additional Technical Data

Fastening Torque (Contact Screw):	M3: (25-30) Ncm
Fastening Torque (Cable Gland):	(150-200) Ncm
Fastening Torque (Attachment):	(50-60) Ncm

Approvals

VDE:	yes
SEV:	yes

Safety & Environmental Compliance

RoHS Compliant:

Notes

Note Derating:	Notice derating
Protection Degree / IP Rating Note:	** only if mounted and locked in combination with Hirschmann / Lumberg Automation connector.
Note: Do not connect or disconnect under load.	

Variants

Item # Item Description		Replacement For
934888100	GDM2106-A0U-10F	ID: 934393100 Name: GDM 2016 schwarz

© 2023 Belden, Inc

All Rights Reserved

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.