

MLX90290 Datasheet

High Speed Factory Trimmed Linear Hall IC

1. Features and Benefits

- Linear Hall Sensor
- Small Size
- High Sensitivity
- High Accuracy
- High Speed
- Fast Start-Up for power gating in Micro-power applications
- Factory Programmed Customization
 - Sensitivity
 - Magnet Thermal Drift Compensation
 - Supply Voltage
- Automotive AEC Q-100 Qualified

2. Application Examples

- Linear Position Sensor
- Rotary Position Sensor
- Current Sensing
- Motor Commutation/Resolving

3. Description

The Melexis MLX90290 is a Second Generation linear Hall-effect sensor designed in mixed signal CMOS technology.

The device integrates a voltage regulator, Hall sensor with advanced offset cancellation system, and an analog output driver, in a single package.

The Output voltage is proportional to the applied magnetic field and to the chip supply voltage (ratiometric). Multiple sensitivity codes & magnet compensation options exist.

The Output Offset Level (Quiescent Level) at zero magnetic field is 50% of the chip supply voltage.

The device is offered in a RoHS compliant Thin Small Outline Transistor (TSOT) for surface mount and UA (TO-92) for Pin Through Hole mount.




Figure 1 Functional Block Diagram MLX90290

Contents

| | |
|--|----|
| 1. Features and Benefits..... | 1 |
| 2. Application Examples..... | 1 |
| 3. Description | 1 |
| 4. Ordering Information | 3 |
| 5. Glossary of Terms..... | 6 |
| 6. Pin Definitions and Descriptions | 6 |
| 7. Absolute Maximum Ratings | 7 |
| 8. General Electrical Specifications | 8 |
| 9. Sensor Specific Specifications | 9 |
| 10. Detailed General Description..... | 11 |
| 10.1. Characteristic Definitions | 11 |
| 11. Application Information..... | 12 |
| 11.1. Typical Application Diagram..... | 12 |
| 11.2. Application Circuit for Harsh and Noisy Environment | 13 |
| 12. Package Information –Example from MLX90290 | 14 |
| 12.1. UA (TO92-3L) Package Information | 14 |
| 12.2. UA (TO92-3L) Hall Plate Location..... | 14 |
| 12.2.1. Trim and form with 2.54mm distance between leads; only available on tape | 15 |
| 12.3. SE (TSOT-3L) Package Information..... | 16 |
| 12.4. SE (TSOT-3L) Hall Plate Location | 16 |
| 13. Standard Information | 17 |
| 14. ESD Precautions..... | 17 |
| 15. Contact..... | 17 |
| 16. Disclaimer..... | 18 |

4. Ordering Information

| Product Code | Temperature Code | Package Code | Option Code | Packing Form Code |
|--------------|------------------|--------------|-------------|-------------------|
| MLX90290 | L | UA | AAA-XYZ | BU |

| | | | | |
|----------|---|----|---------|----|
| MLX90290 | L | SE | AAA-XYZ | RE |
|----------|---|----|---------|----|

Legend:

Temperature Code: L: (-40°C to 150°C)

Package Code: UA: TO-92-3L
SE: TSOT-3L

AAA-XYZ:
AAA = die version

X = V_{DDNOM} and trim & form options for UA package

- See Below Table: Package Options

Y = S

Option Code:

| | | | | | |
|------|-------------|------|----|--------------|--------|
| • 0: | 18.8 mV/mT | @ 5V | Or | 12.408 mV/mT | @ 3.3V |
| • 1: | 25 mV/mT | @ 5V | Or | 16.5 mV/mT | @ 3.3V |
| • 2: | 31.25 mV/mT | @ 5V | Or | 20.625 mV/mT | @ 3.3V |
| • 3: | 50 mV/mT | @ 5V | Or | 33 mV/mT | @ 3.3V |
| • 4: | 100 mV/mT | @ 5V | Or | 66 mV/mT | @ 3.3V |
| • 5: | 39 mV/mT | @ 5V | Or | N/A | @ 3.3V |

Z = TCS

| | |
|------|-------------|
| • 0: | 0 ppm/°C |
| • 1: | 500 ppm/°C |
| • 2: | 2000 ppm/°C |
| • 3: | 650 ppm/°C |

Important: S is expressed as mV/mT for 5V. This sensitivity scales with supply voltage.
E.g. Option 1 with 3.3V VDD supply voltage becomes 16.5mV/mT = $3.3/5 * 25\text{mV/mT}$.

| | Package Options | |
|----------------|------------------------------|---|
| Supply Voltage | SE UA with straight leads | UA with 2.54mm pitch, see section "UA package, trim and form" |
| 3.3 V ± 5 % | X=3 | X=4 |
| 5.0 V ± 10 % | X=5 | X=6 |

Packing Form:
RE = Reel for SE or UA
CR = Radial Tape for UA (Carton Tape on Reel)
CA = Radial Tape for UA (Carton Tape in Ammopack)
BU = Bulk for SE or UA

Ordering example: MLX90290-LUA-AAA-612-CR. This ordering code indicates a 5V supply part in TO92 (UA) component with leads separated to achieve a 2.54mm pitch delivered in Carton Tape on Reel. The sensitivity corresponds to 25mV/mT and a thermal coefficient of +2000 ppm/°C to compensate for the magnet thermal drift (assumed to be a ferrite magnet).

| Ordering Code | Package | Supply Voltage | Absolute Sensitivity | TC | Lead Forming | Packing Form ⁽¹⁾ |
|------------------------|---------|----------------|----------------------------|------------|--------------|-----------------------------|
| MLX90290LSE-AAA-300-RE | TSOT-3L | 3.3V | 12.408mV/mT ⁽²⁾ | 0ppm/°C | N/A | Plastic Tape on Reel |
| MLX90290LSE-AAA-310-RE | TSOT-3L | 3.3V | 16.5mV/mT ⁽²⁾ | 0ppm/°C | N/A | Plastic Tape on Reel |
| MLX90290LSE-AAA-320-RE | TSOT-3L | 3.3V | 20.625mV/mT ⁽²⁾ | 0ppm/°C | N/A | Plastic Tape on Reel |
| MLX90290LSE-AAA-321-RE | TSOT-3L | 3.3V | 20.625mV/mT ⁽²⁾ | 500ppm/°C | N/A | Plastic Tape on Reel |
| MLX90290LSE-AAA-332-RE | TSOT-3L | 3.3V | 33mV/mT ⁽²⁾ | 2000ppm/°C | N/A | Plastic Tape on Reel |
| MLX90290LSE-AAA-510-RE | TSOT-3L | 5V | 25mV/mT | 0ppm/°C | N/A | Plastic Tape on Reel |
| MLX90290LSE-AAA-511-RE | TSOT-3L | 5V | 25mV/mT | 500ppm/°C | N/A | Plastic Tape on Reel |
| MLX90290LSE-AAA-520-RE | TSOT-3L | 5V | 31.25mV/mT | 0ppm/°C | N/A | Plastic Tape on Reel |
| MLX90290LSE-AAA-521-RE | TSOT-3L | 5V | 31.25mV/mT | 500ppm/°C | N/A | Plastic Tape on Reel |
| MLX90290LSE-AAA-522-RE | TSOT-3L | 5V | 31.25mV/mT | 2000ppm/°C | N/A | Plastic Tape on Reel |
| MLX90290LSE-AAA-553-RE | TSOT-3L | 5V | 39mV/mT | 650ppm/°C | N/A | Plastic Tape on Reel |
| MLX90290LSE-AAA-530-RE | TSOT-3L | 5V | 50mV/mT | 0ppm/°C | N/A | Plastic Tape on Reel |
| MLX90290LSE-AAA-531-RE | TSOT-3L | 5V | 50mV/mT | 500ppm/°C | N/A | Plastic Tape on Reel |
| MLX90290LSE-AAA-532-RE | TSOT-3L | 5V | 50mV/mT | 2000ppm/°C | N/A | Plastic Tape on Reel |
| MLX90290LSE-AAA-540-RE | TSOT-3L | 5V | 100mV/mT | 0ppm/°C | N/A | Plastic Tape on Reel |
| MLX90290LUA-AAA-500-BU | TO92-3L | 5V | 18.8mV/mT | 0ppm/°C | Std 1.27mm | Bulk |
| MLX90290LUA-AAA-500-RE | TO92-3L | 5V | 18.8mV/mT | 0ppm/°C | Std 1.27mm | Plastic Tape on Reel |
| MLX90290LUA-AAA-510-BU | TO92-3L | 5V | 25mV/mT | 0ppm/°C | Std 1.27mm | Bulk |
| MLX90290LUA-AAA-510-RE | TO92-3L | 5V | 25mV/mT | 0ppm/°C | Std 1.27mm | Plastic Tape on Reel |

| Ordering Code | Package | Supply Voltage | Absolute Sensitivity | TC | Lead Forming | Packing Form ⁽¹⁾ |
|------------------------|---------|----------------|----------------------|------------|---------------|-----------------------------|
| MLX90290LUA-AAA-511-BU | TO92-3L | 5V | 25mV/mT | 500ppm/°C | Std 1.27mm | Bulk |
| MLX90290LUA-AAA-512-BU | TO92-3L | 5V | 25mV/mT | 2000ppm/°C | Std 1.27mm | Bulk |
| MLX90290LUA-AAA-612-CR | TO92-3L | 5V | 25mV/mT | 2000ppm/°C | 2.54mm spread | Carton Tape on Reel |
| MLX90290LUA-AAA-520-BU | TO92-3L | 5V | 31.25mV/mT | 0ppm/°C | Std 1.27mm | Bulk |
| MLX90290LUA-AAA-520-CR | TO92-3L | 5V | 31.25mV/mT | 0ppm/°C | Std 1.27mm | Carton Tape on Reel |
| MLX90290LUA-AAA-620-CR | TO92-3L | 5V | 31.25mV/mT | 0ppm/°C | 2.54mm spread | Carton Tape on Reel |
| MLX90290LUA-AAA-521-BU | TO92-3L | 5V | 31.25mV/mT | 500ppm/°C | Std 1.27mm | Bulk |
| MLX90290LUA-AAA-522-BU | TO92-3L | 5V | 31.25mV/mT | 2000ppm/°C | Std 1.27mm | Bulk |
| MLX90290LUA-AAA-530-BU | TO92-3L | 5V | 50mV/mT | 0ppm/°C | Std 1.27mm | Bulk |
| MLX90290LUA-AAA-531-BU | TO92-3L | 5V | 50mV/mT | 500ppm/°C | Std 1.27mm | Bulk |
| MLX90290LUA-AAA-631-CA | TO92-3L | 5V | 50 mV/mT | 500ppm/°C | 2.54mm spread | Carton Tape in Ammopack |
| MLX90290LUA-AAA-631-CR | TO92-3L | 5V | 50 mV/mT | 500ppm/°C | 2.54mm spread | Carton Tape on Reel |
| MLX90290LUA-AAA-532-BU | TO92-3L | 5V | 50mV/mT | 2000ppm/°C | Std 1.27mm | Bulk |
| MLX90290LUA-AAA-540-BU | TO92-3L | 5V | 100mV/mT | 0ppm/°C | Std 1.27mm | Bulk |
| MLX90290LUA-AAA-541-BU | TO92-3L | 5V | 100mV/mT | 500ppm/°C | Std 1.27mm | Bulk |
| MLX90290LUA-AAA-542-BU | TO92-3L | 5V | 100mV/mT | 2000ppm/°C | Std 1.27mm | Bulk |
| MLX90290LUA-AAA-553-BU | TO92-3L | 5V | 39mV/mT | 650ppm/°C | Std 1.27mm | Bulk |

Table 1 Available option codes in production

The above option codes are all released in production. An option code refers to the sensitivity and magnet compensation. In order to obtain a not listed option code in Table 1, please contact your local Sales Representative to explore the options of customization during Melexis factory trimming.

- (1) Melexis can provide for a given option code a different packing forms, such as –RE for TSOT-3L surface mount package and –BU, –CR or –CA for TO92-3L through hole package. So, it is possible to obtain a different packing form for a product listed in Table 1.
- (2) Sensitivity scaled for 3.3V supply.

Note: Delivery in bulk (packing form code BU) may cause some parts to have lead pitch and coplanarity deviation due to transport stress.

Especially when a fully automatic assembly process is applied by customer, Melexis recommends ordering parts on cardboard radial tape in ammpack (packing form code CA) or reel (packing form code CR) packing.

5. Glossary of Terms

| Name | Definition |
|-----------|--|
| Tesla [T] | Units of magnetic flux density: 1mT = 10 Gauss |
| ESD | Electro-Static Discharge |
| TSOT | Thin Small Outline Transistor package |
| PSRR | Power Supply Rejection Ratio |
| SMD | Surface Mount Devices |
| THD | Through Hole Device |
| RoHS | Restriction of Hazardous Substances |


Table 2

6. Pin Definitions and Descriptions

| SE Pin № | UA Pin № | Name | Type | Function |
|----------|----------|------|--------|----------------|
| 1 | 1 | VDD | Supply | Supply Voltage |
| 2 | 3 | OUT | I/O | Analog Output |
| 3 | 2 | GND | Ground | Ground |



UA package



SE package

Table 3 Pin Definitions and Descriptions

7. Absolute Maximum Ratings

Operating Characteristics, $V_{DD} = 3.15V$ to $5.5V$, $T_A = -40^{\circ}C$ to $150^{\circ}C$, $C1 \geq 0.1\mu F$ (unless otherwise specified)

| Parameter | Symbol | Value | Units |
|---|-------------|----------------------|-------------|
| Supply Voltage | V_{DD} | -0.3 to 7 | V |
| Supply Current ¹ | I_{DD} | ± 20 | mA |
| Output Voltage | V_{OUT} | -0.3 to $V_{DD}+0.3$ | V |
| Output Current ¹ | I_{OUT} | ± 20 | mA |
| Operating Temperature Range | T_A | -40 to 150 | $^{\circ}C$ |
| Maximum Junction Temperature | T_J | 165 | $^{\circ}C$ |
| Storage Temperature Range | T_S | -55 to 165 | $^{\circ}C$ |
| ESD Sensitivity (Human Body Model) ² | ESD_{HBM} | 8 | kV |
| ESD Sensitivity (Charged Device Model) ³ | ESD_{CDM} | 500 | V |
| Maximum Flux Density | B | > 1000 | mT |

Table 4 Absolute Maximum Ratings

Exceeding the absolute maximum ratings may cause permanent damage. Exposure to absolute maximum-rated conditions for extended periods may affect device reliability.

¹ Including the current flowing through the protection structure. Maximum power dissipation should be also considered

² Human Body Model according AEC-Q100-002 standard

³ Charged Device Model according AEC-Q100-011 standard

8. General Electrical Specifications

Operating Characteristics, $V_{DD} = 3.15V$ to $5.5V$, $T_A = -40^{\circ}C$ to $150^{\circ}C$, $C_1 \geq 0.1\mu F$ (unless otherwise specified)

| Parameter | Symbol | Test Conditions | Min | Typ ⁴ | Max | Units |
|---|--------------|--|-----------------|------------------|-------------------------|---------------|
| Supply Voltage | V_{DD} | Operating | 3.15 | - | 5.5 | V |
| Supply Current | I_{DD} | | 3 | 5 | 8 | mA |
| Reset Voltage | V_{POR} | OUT \rightarrow High Impedance | - | 2.7 | 2.95 | V |
| Load Current Range | I_{OUT} | | -1 | - | 1 | mA |
| Load Resistance Range | R_L | Connected between OUT and GND | 5 | - | Infinite | k Ω |
| Load Capacitor Range ⁵ | C_L | Connected between OUT and GND | 0 | 10 | 100 with $R_S=50\Omega$ | nF |
| Output Saturation Voltage | V_{OSHI} | $I_{OUT} = -1mA$, $B=1.1*(V_{DD} - V_{OQ})/S$ | $V_{DD} - 0.25$ | - | V_{DD} | V |
| | V_{OSHI}^5 | $I_{OUT} = -0.1mA$, $B=1.1*(V_{DD} - V_{OQ})/S$ | $V_{DD} - 0.1$ | - | V_{DD} | V |
| | V_{OSLO} | $I_{OUT} = 1mA$, $B=1.1*(-V_{OQ})/S$ | 0 | - | 0.25 | V |
| | V_{OSLO}^5 | $I_{OUT} = 0.1mA$, $B=1.1*(-V_{OQ})/S$ | 0 | - | 0.1 | V |
| Output Resistance | R_{OUT} | $I_{OUT} = \pm 1mA$ | - | 1.5 | 5 | Ω |
| Power-On Time ^{6,7} | t_{ON} | $V_{DD}=V_{DDNOM}^8$, $B=0.4/S_{REL}$, $dV_{DD}/dt > 2V/\mu s$ | - | 40 | 70 | μs |
| Chopping Frequency | F_{CHOP} | | - | 900 | - | kHz |
| Sample / Update Period | T_{SAMPLE} | $T_{SAMPLE} = 1/F_{CHOP}$ | - | 1.1 | - | μs |
| Power Supply Rejection Ratio ⁵ | PSRR | From 80kHz to 200kHz | 20 | - | - | dB |
| Package Thermal Resistance | R_{THJA} | TSOT-3L | - | 230 | - | $^{\circ}C/W$ |
| Junction to Ambient | | 3-SIP-UA / TO92-UA | - | 180 | - | $^{\circ}C/W$ |

Table 5 : General Electrical Specification

⁴ Typical values are defined at $T_A = 25^{\circ}C$ and $V_{DD} = V_{DDNOM}$

⁵ Guaranteed by design and characterization

⁶ The Power-On Time represents the time from reaching $V_{DD} = 3.15V$ to V_{OUT} settled within $\pm 5\%$ from its final value

⁷ Power-On Slew Rate is not critical for the proper device start-up

⁸ $V_{DDNOM} = 5V$ or $3.3V$ - the value used at trimming

9. Sensor Specific Specifications

Operating Characteristics, $V_{DD} = 3.15V$ to $5.5V$, $T_A = -40^{\circ}C$ to $150^{\circ}C$, $C1 \geq 0.1\mu F$ (unless otherwise specified)

| Parameter | Symbol | Test Conditions | Min | Typ ⁹ | Max | Units |
|-------------------------------------|--------------------------|---|--------------------------------------|--|--------------------------------------|-------------------------|
| Sensitivity Accuracy | ϵS | $T_A=25^{\circ}C$, $V_{DD}=V_{DDNOM}^{10}$ | -5 | - | 5 | % |
| Sensitivity Ratiometry | $\epsilon^R S$ | | -2.5 | - | 2.5 | % / V |
| Linearity | Lin | $V_{DD}=V_{DDNOM}^{10}$ | -1.5 | - | 1.5 | % |
| Symmetry | Sym | $V_{DD}=V_{DDNOM}^{10}$ | -1.5 | - | 1.5 | % |
| Relative Output Offset Level | V_{OQREL} | $B=0mT$, $T_A=25^{\circ}C$, $V_{DD}=V_{DDNOM}^{10}$ | 0.49 | 0.5 | 0.51 | - |
| Thermal Offset Drift | $\epsilon^T V_{OQ}^{11}$ | $B=0mT$, $V_{DD}=V_{DDNOM}^{10}$ S in [mV/mT] | $-(25mV+0.9mT*S)$ | 0 | $+(25mV+0.9mT*S)$ | - |
| Output Offset Ratiometry | $\epsilon^R V_{OQREL}$ | $B=0mT$ | -2.5 | - | 2.5 | % / V |
| Signal Bandwidth | BW | At -3dB, $B<0.4/S_{REL}$, UA package SOT package | 15 ¹² 25 ¹² | 30 ¹² 50 ¹² | - | kHz |
| Signal Phase Shift | PHI | Sine wave magnetic field at $F = 1$ kHz UA package SOT package | - | 3.6 ¹² 2.4 ¹² | 5 ¹² 3.2 ¹² | Degree |
| Sensitivity Range | S | $V_{DD}=V_{DDNOM}^{10}$ | 9.9 15 | - | 66 100 | mV/mT@3.3V mV/mT @5V |
| Sensitivity Temperature Coefficient | TCS | $V_{DD}=V_{DDNOM}^{10}$ | 0 | | 2000 | ppm/ $^{\circ}C$ |

Table 6 Magnetic specification

⁹ Typical values are defined at $T_A = 25^{\circ}C$ and $V_{DD} = V_{DDNOM}$

¹⁰ $V_{DDNOM} = 5V$ or $3.3V$ - the value used at trimming. This sensitivity scales with supply voltage.

E.g. $Y=1$ with $3.3V$ VDD supply voltage becomes $16.5mV/mT = 3.3/5 * 25mV/mT$.

¹¹ Guaranteed by design and characterization

¹² Signal Bandwidth & Signal Phase Shift mentioned here are defined for $Z=1$ & 2 , resp. $500ppm/^{\circ}C$ & $2000ppm/^{\circ}C$. The option code $Z=0$ has internal filtering disabled. Products for $0ppm/^{\circ}C$ are targeted for current measurement applications. Therefore, Bandwidth & Phase Shift are not specified. No internal filter enables a step response time in the order of μs . To get an idea of the phase & amplitude behavior over frequency, use a bode diagram for a 1st order RC filter with the Frequencies specified under "Band width". Also note that Melexis can support you to get an application specific filter setting. Contact your sales contact in such case.

| Parameter | Code | Symbol | Test Conditions | Min | Typ | Max | Units |
|--|-------|----------------------------------|---|------|--------|------|------------|
| Sensitivity Temperature Coefficient | Z = 0 | TCS ₋₄₀ ¹¹ | T _A = -40°C, V _{DD} = V _{DDNOM} ¹⁰ | | 0 | | ppm/°C |
| | | TCS ₁₅₀ ¹³ | T _A = 150°C, V _{DD} = V _{DDNOM} ¹⁰ | | 0 | | ppm/°C |
| | Z = 1 | TCS ₋₄₀ ¹¹ | T _A = -40°C, V _{DD} = V _{DDNOM} ¹⁰ | 0 | 650 | 1300 | ppm/°C |
| | | TCS ₁₅₀ ¹³ | T _A = 150°C, V _{DD} = V _{DDNOM} ¹⁰ | 0 | 500 | 1000 | ppm/°C |
| | Z = 2 | TCS ₋₄₀ ¹¹ | T _A = -40°C, V _{DD} = V _{DDNOM} ¹⁰ | 1100 | 2000 | 2900 | ppm/°C |
| | | TCS ₁₅₀ ¹³ | T _A = 150°C, V _{DD} = V _{DDNOM} ¹⁰ | 1100 | 2000 | 2900 | ppm/°C |
| | Z = 3 | TCS ₋₄₀ ¹¹ | T _A = -40°C, V _{DD} = V _{DDNOM} ¹⁰ | 0 | 650 | 1300 | ppm/°C |
| | | TCS ₁₅₀ ¹³ | T _A = 150°C, V _{DD} = V _{DDNOM} ¹⁰ | 0 | 500 | 1000 | ppm/°C |
| Sensitivity Range (factory trimmed) | Y = 0 | S | V _{DD} = V _{DDNOM} ¹⁰ | | 12.4 | | mV/mT@3.3V |
| | | | | | 18.8 | | mV/mT@5V |
| | Y = 1 | S | V _{DD} = V _{DDNOM} ¹⁰ | | 16.5 | | mV/mT@3.3V |
| | | | | | 25 | | mV/mT@5V |
| | Y = 2 | S | V _{DD} = V _{DDNOM} ¹⁰ | | 20.625 | | mV/mT@3.3V |
| | | | | | 31.25 | | mV/mT@5V |
| | Y = 3 | S | V _{DD} = V _{DDNOM} ¹⁰ | | 33 | | mV/mT@3.3V |
| | | | | | 50 | | mV/mT@5V |
| | Y = 4 | S | V _{DD} = V _{DDNOM} ¹⁰ | | 66 | | mV/mT@3.3V |
| | | | | | 100 | | mV/mT@5V |
| | Y = 5 | S | V _{DD} = V _{DDNOM} ¹⁰ | | N/A | | mV/mT@3.3V |
| | | | | | 39 | | mV/mT@5V |

Table 7 Available Settings

¹³ Guaranteed by correlation with wafer test and characterization

10. Detailed General Description

10.1. Characteristic Definitions

The Sensor DC Output Voltage is defined by:

$$V_{OUT} = V_{DD} \cdot (V_{OQREL} + S_{REL} \cdot B), [V], \text{ where:}$$

$$V_{OQREL} = \frac{V_{OQ}}{V_{DD}}, \left[\frac{V}{V} \right] \text{ is the measured relative quiescent output voltage, its nominal value is 0.5;}$$

$$V_{OQ} = V_{OUT}, [V] \text{ is the measured quiescent output voltage at } B = 0;$$

$$S_{REL} = \frac{S}{V_{DD}} = \frac{\Delta V_{OUT}}{\Delta B} \cdot \frac{1}{V_{DD}}, \left[\frac{1}{T} \right] \text{ is the relative magnetic sensitivity;}$$

$$S = \frac{\Delta V_{OUT}}{\Delta B} = S_{REL} \cdot V_{DD}, \left[\frac{V}{T} \right] \text{ is the magnetic sensitivity at given supply voltage } V_{DD}.$$

Magnetic Sensitivity Temperature Coefficient TCS is defined by:

$$TCS = \frac{S_{REL}(T_A) - S_{REL}(25^{\circ}C)}{S_{REL}(25^{\circ}C) \cdot (T_A - 25^{\circ}C)} \cdot 10^6, \left[\frac{ppm}{^{\circ}C} \right].$$

Magnetic Sensitivity Ratiometry is defined by:

$$\epsilon^R S = \frac{S_{REL}(V_{DD}) - S_{REL}(V_{DDNOM})}{S_{REL}(V_{DDNOM}) \cdot (V_{DD} - V_{DDNOM})} \cdot 100\%, \left[\frac{\%}{V} \right].$$

Linearity for both positive and negative magnetic fields is defined by:

$$Lin = \frac{S_{REL}(B_2) - S_{REL}(B_1)}{S_{REL}(B_1)} \cdot 100\%, [\%], \text{ where } B_1 = \pm \frac{0.2}{S_{REL}}, B_2 = \pm \frac{0.4}{S_{REL}} \text{ and}$$

$$S_{REL}(B_X) = \frac{V_{OUT}(B_X) - V_{OQ}}{B_X \cdot V_{DD}}.$$

Symmetry for positive and negative magnetic fields is defined by:

$$Sym = \frac{S_{REL}(B_2) - S_{REL}(B_1)}{\frac{1}{2}(S_{REL}(B_1) + S_{REL}(B_2))} \cdot 100\%, [\%], \text{ where } B_1 = \frac{0.4}{S_{REL}}, B_2 = -\frac{0.4}{S_{REL}} \text{ and}$$

$$S_{REL}(B_X) = \frac{V_{OUT}(B_X) - V_{OQ}}{B_X \cdot V_{DD}}$$

Output Offset Temperature Drift is defined by:


$$\varepsilon^T V_{OQ} = V_{OQ}(T_A) - V_{OQ}(25^\circ\text{C}), [\text{mV}].$$

Output Offset Ratiometry is calculated by:

$$\varepsilon^R V_{OQREL} = \frac{V_{OQREL}(V_{DD}) - V_{OQREL}(V_{DDNOM})}{V_{OQREL}(V_{DDNOM}) \cdot (V_{DD} - V_{DDNOM})} \cdot 100\%, \left[\frac{\%}{V} \right].$$

11. Application Information

11.1. Typical Application Diagram




Notes:

For proper operation a 100nF or bigger bypass capacitor C1 should be placed as close as possible to the VDD and GND pins of MLX90290.

For embedded applications the components Rs, RL and CL are not required.

11.2. Application Circuit for Harsh and Noisy Environment




Notes:

For proper operation a 100nF or bigger bypass capacitor C1 should be placed as close as possible to the VDD and GND pins of MLX90290. For harsh and noisy environment, a bypass capacitor C2 of 1nF to 10nF can be placed on the output. For improved EMC performance an additional resistance, Rs and capacitors, C3 and C4 placed close to the connector of the module are recommended. Recommended values for: $R_s \geq 50\Omega$, $1\text{nF} \geq C_3 \leq 4.7\text{nF}$, $1\text{nF} \geq C_4 \leq 10\text{nF}$. For embedded applications the components R_L and C_L are not required.

12. Package Information –Example from MLX90290

12.1. UA (TO92-3L) Package Information




| | A | D | E | F | F1 | J | L | L1 | S | b1 | b2 | c | e | e1 |
|-----|------|------|------|------|------|------|------|------|------|------|------|------|------|------|
| min | 2.90 | 4.00 | 1.45 | 0.45 | 0.00 | 2.51 | 14.0 | 0.90 | 0.63 | 0.35 | 0.43 | 0.35 | 2.49 | 1.22 |
| max | 3.10 | 4.20 | 1.55 | 0.66 | 0.15 | 2.72 | 15.0 | 1.10 | 0.84 | 0.44 | 0.53 | 0.44 | 2.59 | 1.32 |

Notes:

1. Dimensions in millimeters (mm) unless noted otherwise.
2. Package dimensions do not include mold flashes and protrusions.
3. Dimension A and D do not include mold gate and side flash (protrusion) of maximum 0.127 mm per side.

12.2. UA (TO92-3L) Hall Plate Location


Hall plate location



Notes

1. All dimensions are in millimeters
2. Mold flashes and protrusion are not included


12.2.1. Trim and form with 2.54mm distance between leads; only available on tape



| Parameter | Component Height | Component Position | Hole Diameter | Hole Position | Hole Pitch | Component Pitch | Right-Left Bending |
|---------------|------------------|--------------------|---------------|---------------|------------|-----------------|--------------------|
| | H1 | P2 | Do | W1 | Po | P1 | ΔP |
| Nominal | 19mm | 6.35mm | 4mm | 9mm | 12.7mm | 12.7mm | ±0.4mm |
| (& Tolerance) | (±0.5) | (±0.4) | (±0.2) | (-0.5; +0.75) | (±0.3) | (±0.3) | |

| Parameter | Lead Spacing | Front-Rear Bending | Tape Width | Adhesive Tape Width | Adhesive to Carrier Tape Gap | Vertical Lead Length | Component Height Top |
|---------------|--------------|--------------------|------------|---------------------|------------------------------|----------------------|----------------------|
| | F1 & F2 | ΔH | W | Wo | W2 | H0 | H2 |
| Nominal | 2.54mm | ±0.3deg | 18mm | 6mm | 0.5mm | 15.5mm (±0.5) | 22.0mm (±0.8mm) |
| (& Tolerance) | (±0.25mm) | | (±0.5) | (±0.2) | (-0.5; +0.3) | | |

12.3. SE (TSOT-3L) Package Information



Notes:

1. All dimensions are in millimeters
2. Outermost plastic extreme width does not include mold flash or protrusions. Mold flash and protrusions shall not exceed 0.15mm per side.
3. Outermost plastic extreme length does not include mold flash or protrusions. Mold flash and protrusions shall not exceed 0.25mm per side.
4. The lead width dimension does not include dambar protrusion. Allowable dambar protrusion shall be 0.07mm total in excess of the lead width dimension at maximum material condition.
5. Dimension is the length of terminal for soldering to a substrate.
6. Formed lead shall be planar with respect to one another with 0.076mm at seating plane.

Marking:

Top side :

90XXX

XXX: Last three digits of the lot

Bottom side:

WWYY

WW: Calendar Week


YY: Calendar Year

| | A | A1 | A2 | D | E | E1 | L | b | c | e | e1 | α |
|-----|------|-------|------|------|------|------|------|------|------|------|------|----------|
| min | – | 0.025 | 0.85 | 2.80 | 2.60 | 1.50 | 0.30 | 0.30 | 0.10 | 0.95 | 1.90 | 0° |
| max | 1.00 | 0.10 | 0.90 | 3.00 | 3.00 | 1.70 | 0.50 | 0.45 | 0.20 | BSC | BSC | 8° |

Notes:

1. Dimension "D" and "E1" do not include mold flash or protrusions. Mold flash or protrusion shall not exceed 0.15mm on "D" and 0.25mm on "E" per side.
2. Dimension "b" does not include dambar protrusion.

12.4. SE (TSOT-3L) Hall Plate Location



13. Standard Information

Our products are classified and qualified regarding soldering technology, solderability and moisture sensitivity level according to standards in place in Semiconductor industry.

For further details about test method references and for compliance verification of selected soldering method for product integration, Melexis recommends reviewing on our web site the General Guidelines [soldering recommendation](#). For all soldering technologies deviating from the one mentioned in above document (regarding peak temperature, temperature gradient, temperature profile, etc.), additional classification and qualification tests have to be agreed upon with Melexis.

For package technology embedding trim and form post-delivery capability, Melexis recommends to consult the dedicated trim & form recommendation application note: [lead trimming and forming recommendations](#).

Melexis is contributing to global environmental conservation by promoting **lead free** solutions. For more information on qualifications of **RoHS** compliant products (RoHS = European directive on the Restriction Of the use of certain Hazardous Substances) please visit the quality page on our website: <http://www.melexis.com/en/quality-environment>.

14. ESD Precautions

Electronic semiconductor products are sensitive to Electro Static Discharge (ESD).

Always observe Electro Static Discharge control procedures whenever handling semiconductor products.

15. Contact

For the latest version of this document, go to our website at www.melexis.com.

For additional information, please contact our [Direct Sales team](#) and get help for your specific needs:

| | |
|----------------|--|
| Europe, Africa | Email : sales_europe@melexis.com |
| Americas | Email : sales_usa@melexis.com |
| Asia | Email : sales_asia@melexis.com |

16. Disclaimer

The content of this document is believed to be correct and accurate. However, the content of this document is furnished "as is" for informational use only and no representation, nor warranty is provided by Melexis about its accuracy, nor about the results of its implementation. Melexis assumes no responsibility or liability for any errors or inaccuracies that may appear in this document. Customer will follow the practices contained in this document under its sole responsibility. This documentation is in fact provided without warranty, term, or condition of any kind, either implied or expressed, including but not limited to warranties of merchantability, satisfactory quality, non-infringement, and fitness for purpose. Melexis, its employees and agents and its affiliates' and their employees and agents will not be responsible for any loss, however arising, from the use of, or reliance on this document. Notwithstanding the foregoing, contractual obligations expressly undertaken in writing by Melexis prevail over this disclaimer.

This document is subject to change without notice, and should not be construed as a commitment by Melexis. Therefore, before placing orders or prior to designing the product into a system, users or any third party should obtain the latest version of the relevant information. Users or any third party must determine the suitability of the product described in this document for its application, including the level of reliability required and determine whether it is fit for a particular purpose.

This document as well as the product here described may be subject to export control regulations. Be aware that export might require a prior authorization from competent authorities. The product is not designed, authorized or warranted to be suitable in applications requiring extended temperature range and/or unusual environmental requirements. High reliability applications, such as medical life-support or life-sustaining equipment or avionics application are specifically excluded by Melexis. The product may not be used for the following applications subject to export control regulations: the development, production, processing, operation, maintenance, storage, recognition or proliferation of:

1. chemical, biological or nuclear weapons, or for the development, production, maintenance or storage of missiles for such weapons;
2. civil firearms, including spare parts or ammunition for such arms;
3. defense related products, or other material for military use or for law enforcement;
4. any applications that, alone or in combination with other goods, substances or organisms could cause serious harm to persons or goods and that can be used as a means of violence in an armed conflict or any similar violent situation.

No license nor any other right or interest is granted to any of Melexis' or third party's intellectual property rights.

If this document is marked "restricted" or with similar words, or if in any case the content of this document is to be reasonably understood as being confidential, the recipient of this document shall not communicate, nor disclose to any third party, any part of the document without Melexis' express written consent. The recipient shall take all necessary measures to apply and preserve the confidential character of the document. In particular, the recipient shall (i) hold document in confidence with at least the same degree of care by which it maintains the confidentiality of its own proprietary and confidential information, but no less than reasonable care; (ii) restrict the disclosure of the document solely to its employees for the purpose for which this document was received, on a strictly need to know basis and providing that such persons to whom the document is disclosed are bound by confidentiality terms substantially similar to those in this disclaimer; (iii) use the document only in connection with the purpose for which this document was received, and reproduce document only to the extent necessary for such purposes; (iv) not use the document for commercial purposes or to the detriment of Melexis or its customers. The confidentiality obligations set forth in this disclaimer will have indefinite duration and in any case they will be effective for no less than 10 years from the receipt of this document.

This disclaimer will be governed by and construed in accordance with Belgian law and any disputes relating to this disclaimer will be subject to the exclusive jurisdiction of the courts of Brussels, Belgium.

The invalidity or ineffectiveness of any of the provisions of this disclaimer does not affect the validity or effectiveness of the other provisions. The previous versions of this document are repealed.

Melexis © - No part of this document may be reproduced without the prior written consent of Melexis. (2021)

IATF 16949 and ISO 14001 Certified

Revision History Table

| | | |
|---------|-------------|---|
| Rev 001 | 6-Oct-2014 | Document Creation |
| Rev 002 | 22-May-2019 | Update to new Melexis branding template |
| Rev 003 | 15-Apr-2020 | Updated UA package outline drawing to current format Added versions placed into production since latest update Updated block diagram to standard Melexis format and colors Added Automotive AEC Q-100 qualified note under "Features and Benefits" |
| | 23-Apr-2020 | Updated 3D package drawings in section 6 |
| Rev 004 | 1-Mar-2021 | Added MLX90290LSE-AAA-522-RE to the standard available options Package outline dimensions for UA package updated Hall plate location updated from 0.44±0.04 to 0.44±0.03 Added note regarding lead coplanarity and pitch in bulk packaging |
| Rev 005 | 21-Jun-2021 | Added MLX90290LUA-AAA-553-BU to the standard available options Converted UA tape drawing to vector format for clarity |