

MISUMI USA will close early on Friday, December 2. Orders placed after 6:00 p.m. Eastern Time will be processed when we return Monday, December 5. Online quoting and order requests are available. Representatives are available to answer toll free phone calls until 9:00 p.m. Eastern Time. We thank you for your patience and apologize for any inconvenience.

MISUMI Home > Electrical & Controls > PC Parts > Power Supply for PC > Power Supply for PC > ATX 300W

How can we improve?

ATX 300W



Silent-Compatible

ATX Power Supply

FEATURES

- Compared to conventional power supplies, high reliability and long life are achieved by increasing the derating factor of the parts.
- Peak 300 W, continuous 260 W output.

CAUTION

External appearance and specifications are subject to change without notice.

Configure

Clear All

Completed

Specification/Dimensions

Representative Standard

UL

CSA

Clear

Days to Ship

ALL

4 Days or Less

Part Number PCPS-PCSA300-P4-R

Add

Copy

Similar Products

Download Product Details

Configured Specifications			
Type	ATX Power Supply	Capacity(W)	300
Serial ATA	N/A	For Internal Connection Cable Detach	Improper
Representative Standard	UL / CSA	Vertical(mm)	86
Width(mm)	150	Depth(mm)	140

Order Qty.

1

Quantity	Standard Unit Price	Days to Ship
0-5	-	Quote
6-	-	Quote

NOTE: Days to Ship above are subject to change depending upon availability.

Please check Ship Date below for the specific quantity needed.

Quantity

1

Unit Price

Total

Ship Date

Ship Date is valid until 8:00 pm (Eastern Time).

Order Now

Add to Cart

What is Volume Discount Rate?

About Express Service

Specifications

Part Number	ATX Power Supply Connector	For CPU Connector
PCPS-PCSA300-P4-R	20 Pin	4 Pin

Sales: Misumi / Manufacturer: Nipron Co., Ltd.

More Information


Specifications

Manufacturer Part Number		PCSA-300P-X2V					
Input	AC	85 - 264 V (Autoswitching) (47 - 63 Hz)					
Output		+3.3V	+5V	+12V	-5V	-12V	+5 Vsb
	Maximum Load Current (Continuous)	15A	25A	10A	0.5A	0.5A	1A
		Total 25 A					
		Total 125 W					
	Maximum Output Power (Continuous)		Total 258.5 W				
	Maximum Load Current (Peak)	20A	30A	15A	0.5A	0.5A	1.5A
		Total 30 A					
		Total 280 W					
	Maximum Output Power (Peak)		Total 296 W				
	Minimum Load Current		-	2A	-		-
Connectors		For Main Board x 1, for Peripheral x 5, for FDD x 1, for CPU x 1, * AUX x 1					
Standard		UL, CSA, EN					
Operating Environment		Temperature: 0 - 60°C					
Weight / External Dimensions (mm)		1.8 kg, 150 (W) x 140 (D) x 86 (H)					

* Connector for AUX 4-pin fan.

Basic Information

Type	ATX Power Supply	Capacity(W)	300	Serial ATA	N/A
For Internal Connection Cable Detach	Improper	Vertical(mm)	86	Width(mm)	150
Depth(mm)	140				



Send a Message ^