

Part Number: 1202530226

**Product Description : Contrinex Inductive** Sensor, M12 Housing, 2mm Operating Distance, Embeddable, NPN, NO, 4-pin M12 Connector, 60mm Housing Length

Series Number: 120253

Status: Active

**Product Category :** Inductive and Photoelectric Sensors

**Engineering Number: DW-AS-601-M12** 



#### **Documents & Resources**

**Specifications** 

1202530222-000.pdf

# **Product Environment Compliance**

### Compliance

GADSL/IMDS	Not Relevant
China RoHS	<b>®</b>
EU ELV	Not Relevant
Low-Halogen Status	Not Reviewed per IEC 61249-2-21
REACH SVHC	Not Reviewed per D(2024)6225-DC (07 Nov 2024)
EU RoHS	Compliant with Exemption 6(c) per EU 2015/863

## Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

#### Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

# **Part Details**

# General

Status	Active
Category	Inductive and Photoelectric Sensors
Series	120253
Description	Contrinex Inductive Sensor, M12 Housing, 2mm Operating Distance, Embeddable, NPN, NO, 4-pin M12 Connector, 60mm Housing Length
IP Rating	IP67
Product Name	Contrinex
Туре	Inductive
UPC	191130063963

# Electrical

Output	NO
Polarity	NPN
Switching Frequency	≤ 3000 Hz

# Physical

Connection	Connector (M12, 4-pin)
Length	60mm
Material - Housing	Nickel Plated Brass
Material - Sensing Face	PBTP
Mounting Style	Embeddable
Operating Distance	2mm
Output	NO
Sensor Housing Size	M12
Temperature Range - Operating	-25° to +70°C