



**Part Number :** [1202530249](#)  
**Product Description :** Contrinex Inductive Sensor, M18 Housing, 8mm Operating Distance, Non-embeddable, PNP, NC, 2m 3-wire PVC Cable, 50mm Housing Length  
**Series Number :** 120253  
**Status :** Active  
**Product Category :** Inductive and Photoelectric Sensors  
**Engineering Number :** DW-AD-614-M18




## Documents & Resources

**Specifications**  
[1202530246-000.pdf](#)

## Product Environment Compliance

### Compliance

|                    |   |
|--------------------|---|
| GADSL/IMDS         | Not Relevant  |
| China RoHS         |  |
| EU ELV             | Not Relevant  |
| Low-Halogen Status | Not Reviewed per IEC 61249-2-21   |
| REACH SVHC         | Not Reviewed per D(2024)6225-DC (07 Nov 2024)   |
| EU RoHS            | Compliant with Exemption 6(c) per EU 2015/863   |

### Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

### Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

Part Details

General

|              |  |
|--------------|--|
| Status       | Active   |
| Category     | Inductive and Photoelectric Sensors  |
| Series       | 120253   |
| Description  | Contrinex Inductive Sensor, M18 Housing, 8mm Operating Distance, Non-embeddable, PNP, NC, 2m 3-wire PVC Cable, 50mm Housing Length |
| IP Rating    | IP67   |
| Product Name | Contrinex  |
| Type         | Inductive  |
| UPC          | 191130064199   |

Electrical

|                     |           |
|---------------------|-----------|
| Output              | NC        |
| Polarity            | PNP       |
| Switching Frequency | ≤ 2000 Hz |

Physical

|                               |                        |
|-------------------------------|------------------------|
| Connection                    | Cable (PVC 2m, 3-wire) |
| Length                        | 50mm                   |
| Material - Housing            | Nickel Plated Brass    |
| Material - Sensing Face       | PBTP                   |
| Mounting Style                | Non-embeddable         |
| Operating Distance            | 8mm                    |
| Output                        | NC                     |
| Sensor Housing Size           | M18                    |
| Temperature Range - Operating | -25° to +70°C          |