

Part Number : <u>1202530304</u> Product Description : Contrinex Inductive Sensor, M12 Housing, 4mm Operating Distance, Non-embeddable, PNP, NO, 2m 3wire PVC Cable, 35mm Housing Length Series Number : 120253 Status : Active Product Category : Inductive and Photoelectric Sensors

Engineering Number : DW-AD-613-M12-120



#### **Documents & Resources**

Specifications 1202530302-000.pdf

## **Product Environment Compliance**

#### Compliance

GADSL/IMDS	Not Relevant
China RoHS	<b>6</b>
EU ELV	Not Relevant
Low-Halogen Status	Not Reviewed per IEC 61249-2-21
REACH SVHC	Not Reviewed per D(2024)6225-DC (07 Nov 2024)
EU RoHS	Compliant with Exemption 6(c) per EU 2015/863

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

# **Part Details**

### General

Status	Active
Category	Inductive and Photoelectric Sensors
Series	120253
Description	Contrinex Inductive Sensor, M12 Housing, 4mm Operating Distance, Non-embeddable, PNP, NO, 2m 3- wire PVC Cable, 35mm Housing Length
IP Rating	IP67
Product Name	Contrinex
Туре	Inductive
UPC	191130061594

## Electrical

Output	NO
Polarity	PNP
Switching Frequency	≤ 2000 Hz

# Physical

Connection	Cable (PVC 2m, 3-wire)
Length	35mm
Material - Housing	Nickel Plated Brass
Material - Sensing Face	PBTP
Mounting Style	Non-embeddable
Operating Distance	4mm
Output	NO
Sensor Housing Size	M12
Temperature Range - Operating	-25° to +70°C