

Part Number: 1202530366

Product Description: Contrinex Inductive Sensor, M8 Housing, 4mm Operating Distance, Non-embeddable, NPN, NO, 2m 3-

wire PVC Cable, 35mm Housing Length Series Number: 120253

Status: Active

Product Category : Inductive and Photoelectric Sensors

Engineering Number: DW-AD-631-M8



Documents & Resources

Specifications

1202530366-000.pdf

Product Environment Compliance

Compliance

GADSL/IMDS	Not Relevant
China RoHS	•
EU ELV	Not Relevant
Low-Halogen Status	Not Reviewed per IEC 61249-2-21
REACH SVHC	Not Reviewed per D(2024)6225-DC (07 Nov 2024)
EU RoHS	Compliant per EU 2015/863

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

Part Details

General

Status	Active
Category	Inductive and Photoelectric Sensors
Series	120253
Description	Contrinex Inductive Sensor, M8 Housing, 4mm Operating Distance, Non-embeddable, NPN, NO, 2m 3- wire PVC Cable, 35mm Housing Length
IP Rating	IP67
Product Name	Contrinex
Туре	Inductive
UPC	191130066018

Electrical

Output	NO
Polarity	NPN
Switching Frequency	≤ 3500 Hz

Physical

Connection	Cable (PVC 2m, 3-wire)
Length	35mm
Material - Housing	Stainless Steel
Material - Sensing Face	РВТР
Mounting Style	Non-embeddable
Operating Distance	4mm
Output	NO
Sensor Housing Size	M8
Temperature Range - Operating	-25° to +70°C