

Part Number : <u>1202530412</u> Product Description : Contrinex Inductive Sensor, 6.5mm Diameter Smooth Housing, 2mm Operating Distance, Embeddable, PNP, NO, 2m 3-wire PVC Cable, 16mm Housing Length Series Number : 120253 Status : Active Product Category : Inductive and Photoelectric Sensors Engineering Number : DW-AD-623-065-120



### Documents & Resources

Specifications 1202530410-000.pdf

## **Product Environment Compliance**

#### Compliance

GADSL/IMDS	Not Relevant
China RoHS	®
EU ELV	Not Relevant
Low-Halogen Status	Not Reviewed per IEC 61249-2-21
REACH SVHC	Not Reviewed per D(2024)6225-DC (07 Nov 2024)
EU RoHS	Compliant per EU 2015/863

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

# **Part Details**

### General

Status	Active
Category	Inductive and Photoelectric Sensors
Series	120253
Description	Contrinex Inductive Sensor, 6.5mm Diameter Smooth Housing, 2mm Operating Distance, Embeddable, PNP, NO, 2m 3-wire PVC Cable, 16mm Housing Length
IP Rating	IP67
Product Name	Contrinex
Туре	Inductive
UPC	191130066872

## Electrical

Output	NO
Polarity	PNP
Switching Frequency	≤ 5000 Hz

# Physical

Connection	Cable (PVC 2m, 3-wire)
Length	16mm
Material - Housing	Stainless Steel
Material - Sensing Face	PA12
Mounting Style	Embeddable
Operating Distance	2mm
Output	NO
Sensor Housing Size	6.5mm dia. (smooth)
Temperature Range - Operating	-25° to +70°C