



**Part Number :** [1202530499](#)  
**Product Description :** Contrinex Inductive Sensor, 3mm Diameter Short and Smooth Housing, 1mm Operating Distance, Embeddable, PNP, NO, 2m 3-wire PUR Cable, 12mm Housing Length  
**Series Number :** 120253  
**Status :** Active  
**Product Category :** Inductive and Photoelectric Sensors  
**Engineering Number :** DW-AD-623-03-960



## Documents & Resources

**Specifications**  
[1202530498-000.pdf](#)

## Product Environment Compliance

### Compliance

GADSL/IMDS	Not Relevant
China RoHS	
EU ELV	Not Relevant
Low-Halogen Status	Not Reviewed per IEC 61249-2-21
REACH SVHC	Not Reviewed per D(2024)6225-DC (07 Nov 2024)
EU RoHS	Compliant per EU 2015/863

### Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

### Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

## Part Details

### General

Status	Active
Category	Inductive and Photoelectric Sensors
Series	120253
Description	Contrinex Inductive Sensor, 3mm Diameter Short and Smooth Housing, 1mm Operating Distance, Embeddable, PNP, NO, 2m 3-wire PUR Cable, 12mm Housing Length
IP Rating	IP67
Product Name	Contrinex
Type	Inductive
UPC	191130068647

### Electrical

Output	NO
Polarity	PNP
Switching Frequency	≤ 8000 Hz

### Physical

Connection	Cable (PUR 2m, 3-wire)
Length	12mm
Material - Housing	Stainless Steel
Material - Sensing Face	POM
Mounting Style	Embeddable
Operating Distance	1mm
Output	NO
Sensor Housing Size	3mm dia. (short and smooth)
Temperature Range - Operating	-25° to +70°C