

Part Number: 1202530528

Product Description: Contrinex Inductive Sensor, M5 Housing, 1.5mm Operating Distance, Embeddable, PNP, NC, 3-pin M8 Connector, 38mm Housing Length

Series Number: 120253

Status: Active

**Product Category :** Inductive and Photoelectric Sensors

**Engineering Number: DW-AS-624-M5** 



#### **Documents & Resources**

**Specifications** 

1202530521-000.pdf

## **Product Environment Compliance**

#### Compliance

GADSL/IMDS	Not Relevant
China RoHS	<b>©</b>
EU ELV	Not Relevant
Low-Halogen Status	Not Reviewed per IEC 61249-2-21
REACH SVHC	Not Reviewed per D(2024)6225-DC (07 Nov 2024)
EU RoHS	Compliant per EU 2015/863

#### Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

#### Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

# **Part Details**

## General

Status	Active
Category	Inductive and Photoelectric Sensors
Series	120253
Description	Contrinex Inductive Sensor, M5 Housing, 1.5mm Operating Distance, Embeddable, PNP, NC, 3- pin M8 Connector, 38mm Housing Length
IP Rating	IP67
Product Name	Contrinex
Туре	Inductive
UPC	191130069231

# Electrical

Output	NC
Polarity	PNP
Switching Frequency	≤ 3000 Hz

# Physical

Connection	Connector (M8, 3-pin)
Length	38mm
Material - Housing	Stainless Steel
Material - Sensing Face	POM
Mounting Style	Embeddable
Operating Distance	1.5mm
Output	NC
Sensor Housing Size	M5
Temperature Range - Operating	-25° to +70°C