



**Part Number :** [1202530542](#)  
**Product Description :** Contrinex Inductive Sensor, M8 Fully Stainless Steel, 6mm Operating Distance, Non-embeddable, NPN, NC, 2m 3-wire PUR Cable, 45mm Housing Length  
**Series Number :** 120253  
**Status :** Active  
**Product Category :** Inductive and Photoelectric Sensors  
**Engineering Number :** DW-AD-712-M8



Documents & Resources

Specifications  
[1202530541-000.pdf](#)

Product Environment Compliance

Compliance

GADSL/IMDS	Not Relevant
China RoHS	
EU ELV	Not Relevant
Low-Halogen Status	Not Reviewed per IEC 61249-2-21
REACH SVHC	Not Reviewed per D(2024)6225-DC (07 Nov 2024)
EU RoHS	Compliant per EU 2015/863

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

## Part Details

### General

Status	Active
Category	Inductive and Photoelectric Sensors
Series	120253
Description	Contrinex Inductive Sensor, M8 Fully Stainless Steel, 6mm Operating Distance, Non-embeddable, NPN, NC, 2m 3-wire PUR Cable, 45mm Housing Length
IP Rating	IP68, IP69K
Product Name	Contrinex
Type	Inductive
UPC	191130069477

### Electrical

Output	NC
Polarity	NPN
Switching Frequency	≤ 700 Hz

### Physical

Connection	Cable (PUR 2m, 3-wire)
Length	45mm
Material - Housing	Stainless Steel
Material - Sensing Face	Stainless Steel
Mounting Style	Non-embeddable
Operating Distance	6mm
Output	NC
Sensor Housing Size	M8
Temperature Range - Operating	-25° to +85°C