



**Part Number :** [1202530629](#)  
**Product Description :** Contrinex Inductive Sensor, M12 Fully Stainless Steel, 6mm Operating Distance, Embeddable, NPN, NO, 4-pin M12 Connector, 60mm Housing Length  
**Series Number :** 120253  
**Status :** Active  
**Product Category :** Inductive and Photoelectric Sensors  
**Engineering Number :** DW-LS-701-M12



## Documents & Resources

**Specifications**  
[1202530625-000.pdf](#)

## Product Environment Compliance

### Compliance

|                    |   |
|--------------------|---|
| GADSL/IMDS         | Not Relevant  |
| China RoHS         |  |
| EU ELV             | Not Relevant  |
| Low-Halogen Status | Not Reviewed per IEC 61249-2-21   |
| REACH SVHC         | Not Reviewed per D(2024)6225-DC (07 Nov 2024)   |
| EU RoHS            | Compliant per EU 2015/863   |

### Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

### Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

Part Details

General

|              |  |
|--------------|--|
| Status       | Active   |
| Category     | Inductive and Photoelectric Sensors  |
| Series       | 120253   |
| Description  | Contrinex Inductive Sensor, M12 Fully Stainless Steel, 6mm Operating Distance, Embeddable, NPN, NO, 4-pin M12 Connector, 60mm Housing Length |
| IP Rating    | IP68, IP69K  |
| Product Name | Contrinex  |
| Type         | Inductive  |
| UPC          | 191130065004   |

Electrical

|                     |          |
|---------------------|----------|
| Output              | NO       |
| Polarity            | NPN      |
| Switching Frequency | ≤ 600 Hz |

Physical

|                               |                        |
|-------------------------------|------------------------|
| Connection                    | Connector (M12, 4-pin) |
| Length                        | 60mm                   |
| Material - Housing            | Stainless Steel        |
| Material - Sensing Face       | Stainless Steel        |
| Mounting Style                | Embeddable             |
| Operating Distance            | 6mm                    |
| Output                        | NO                     |
| Sensor Housing Size           | M12                    |
| Temperature Range - Operating | -25° to +85°C          |