



Part Number : [1202530639](#)
Product Description : Contrinex Inductive Sensor, M12 Fully Stainless Steel, 10mm Operating Distance, Non-embeddable, PNP, NO, 4-pin M12 Connector, 60mm Housing Length
Series Number : 120253
Status : Active
Product Category : Inductive and Photoelectric Sensors
Engineering Number : DW-LS-713-M12




Documents & Resources

Specifications
[1202530633-000.pdf](#)

Product Environment Compliance

Compliance

| | |
|--------------------|---|
| GADSL/IMDS | Not Relevant |
| China RoHS |  |
| EU ELV | Not Relevant |
| Low-Halogen Status | Not Reviewed per IEC 61249-2-21 |
| REACH SVHC | Not Reviewed per D(2024)6225-DC (07 Nov 2024) |
| EU RoHS | Compliant per EU 2015/863 |

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

Part Details

General

| | |
|--------------|---|
| Status | Active |
| Category | Inductive and Photoelectric Sensors |
| Series | 120253 |
| Description | Contrinex Inductive Sensor, M12 Fully Stainless Steel, 10mm Operating Distance, Non-embeddable, PNP, NO, 4-pin M12 Connector, 60mm Housing Length |
| IP Rating | IP68, IP69K |
| Product Name | Contrinex |
| Type | Inductive |
| UPC | 191130065417 |

Electrical

| | |
|---------------------|----------|
| Output | NO |
| Polarity | PNP |
| Switching Frequency | ≤ 400 Hz |

Physical

| | |
|-------------------------------|------------------------|
| Connection | Connector (M12, 4-pin) |
| Length | 60mm |
| Material - Housing | Stainless Steel |
| Material - Sensing Face | Stainless Steel |
| Mounting Style | Non-embeddable |
| Operating Distance | 10mm |
| Output | NO |
| Sensor Housing Size | M12 |
| Temperature Range - Operating | -25° to +85°C |