



Part Number : [1202530668](#)
Product Description : Contrinex Inductive Sensor, M30 Fully Stainless Steel, 40mm Operating Distance, Non-embeddable, PNP, NC, 2m 3-wire TPE Cable, 70.2mm Housing Length
Series Number : 120253
Status : Active
Product Category : Inductive and Photoelectric Sensors
Engineering Number : DW-LD-714-M30




Documents & Resources

Specifications
[1202530665-000.pdf](#)

Product Environment Compliance

Compliance

GADSL/IMDS	Not Relevant
China RoHS	
EU ELV	Not Relevant
Low-Halogen Status	Not Reviewed per IEC 61249-2-21
REACH SVHC	Not Reviewed per D(2024)6225-DC (07 Nov 2024)
EU RoHS	Compliant per EU 2015/863

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

Part Details

General

Status	Active
Category	Inductive and Photoelectric Sensors
Series	120253
Description	Contrinex Inductive Sensor, M30 Fully Stainless Steel, 40mm Operating Distance, Non-embeddable, PNP, NC, 2m 3-wire TPE Cable, 70.2mm Housing Length
IP Rating	IP68, IP69K
Product Name	Contrinex
Type	Inductive
UPC	191130065981

Electrical

Output	NC
Polarity	PNP
Switching Frequency	≤ 90 Hz

Physical

Connection	Cable (TPE-S 2m, 3-wire)
Length	70.2mm
Material - Housing	Stainless Steel
Material - Sensing Face	Stainless Steel
Mounting Style	Non-embeddable
Operating Distance	40mm
Output	NC
Sensor Housing Size	M30
Temperature Range - Operating	-25° to +85°C