

Part Number : <u>1202540094</u> Product Description : Contrinex Photoelectric Sensor, M5 Housing, Diffuse, 10mm Operating Distance, NPN, Light-ON, 2m 3-wire PVC Cable, 35mm Housing Length Series Number : 120254 Status : Active Product Category : Inductive and Photoelectric Sensors

Engineering Number: LTR-M05MA-NSK-301



# Documents & Resources

Specifications 1202540094-000.pdf

## **Product Environment Compliance**

#### Compliance

GADSL/IMDS	Not Relevant
China RoHS	®
EU ELV	Not Relevant
Low-Halogen Status	Not Reviewed per IEC 61249-2-21
REACH SVHC	Not Reviewed per D(2024)6225-DC (07 Nov 2024)
EU RoHS	Compliant per EU 2015/863

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

# Part Details

#### General

Status	Active
Category	Inductive and Photoelectric Sensors
Series	120254
Description	Contrinex Photoelectric Sensor, M5 Housing, Diffuse, 10mm Operating Distance, NPN, Light-ON, 2m 3-wire PVC Cable, 35mm Housing Length
IP Rating	IP67
Operating Principle	Diffuse
Product Name	Contrinex
Туре	Photoelectric
UPC	191130068005

### Electrical

Output	Light-ON
Polarity	NPN
Switching Frequency	≤ 250 Hz

# Physical

Connection	Cable (PVC 2m, 3-wire)
Length	35mm
Material - Housing	Stainless Steel
Material - Window	Sapphire
Operating Distance	10mm
Output	Light-ON
Sensor Housing Size	M5
Temperature Range - Operating	0° to +55°C