



Part Number : 1202540017

Series Number : 120254

Product Category : Inductive and Photoelectric Sensors

Product Description : Contrinex Photoelectric Sensor, C12 (13.5 x 21.8mm) Housing, Background Suppression, 1 - 36mm Operating Distance, NPN, Light-ON, 0.2m 3-wire PVC Cable, 3-pin M8 Connector

Status : Active

Engineering Number : LHR-C12PA-NMV-301

Documents & Resources

Specifications

Product Specification 1202540014-000.pdf

Product Environment Compliance

Compliance

GADSL/IMDS	Not Relevant
China RoHS	
EU ELV	Not Relevant
Low-Halogen Status	Not Reviewed per IEC 61249-2-21
REACH SVHC	Not Reviewed per D(2024)4144-DC (27 June 2024)
EU RoHS	Compliant per EU 2015/863

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

EU RoHS Certificate of Compliance

Part Details

## General

Status	Active
Category	Inductive and Photoelectric Sensors
Series	120254
Description	Contrinex Photoelectric Sensor, C12 (13.5 x 21.8mm) Housing, Background Suppression, 1 - 36mm Operating Distance, NPN, Light-ON, 0.2m 3-wire PVC Cable, 3-pin M8 Connector
IP Rating	IP67
Operating Principle	Background Suppression
Product Family	Contrinex Inductive and Photoelectric Sensors
Product Name	Contrinex
Type	Photoelectric
UPC	191130066537

## Electrical

Polarity	NPN
Switching Frequency	≤ 800 Hz

## Physical

Connection	Cable (PVC 0.2m, 3-wire), Connector (M8, 3-pin)
Housing Size	13.5 x 21.8mm
Material - Housing	ABS
Material - Window	PMMA
Operating Distance	1 - 36mm
Output	Light-ON
Sensor Housing Size	C12
Temperature Range - Operating	-20° to +50°C