

Part Number : 1202540059

Series Number : 120254 Product Category : Inductive and Photoelectric Sensors Product Description : Contrinex Photoelectric Sensor, 4155 (40 x 50mm) Housing, Color Sensor, 30 - 40mm Operating Distance, PNP, 3 Outputs Programmable, Teach Sensitivity Adjustment, 5-pin M12 Connector Status : Active

Engineering Number : FTS-4155-303

### **Documents & Resources**

#### Specifications

Product Specification 1202540058-000.pdf

## **Product Environment Compliance**

#### Compliance

GADSL/IMDS	Not Relevant
China RoHS	©
EU ELV	Not Relevant
Low-Halogen Status	Not Reviewed per IEC 61249-2-21
REACH SVHC	Not Reviewed per D(2024)4144-DC (27 June 2024)
EU RoHS	Compliant per EU 2015/863

#### Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

EU RoHS Certificate of Compliance

## General

Status	Active
Category	Inductive and Photoelectric Sensors
Series	120254
Description	Contrinex Photoelectric Sensor, 4155 (40 x 50mm) Housing, Color Sensor, 30 - 40mm Operating Distance, PNP, 3 Outputs Programmable, Teach Sensitivity Adjustment, 5-pin M12 Connector
IP Rating	IP67
Operating Principle	Color
Product Family	Contrinex Inductive and Photoelectric Sensors
Product Name	Contrinex
Туре	Photoelectric
UPC	191130067350

# Electrical

Polarity	PNP
Switching Frequency	≤ 1250 / 4000 Hz

# Physical

Connection	Connector (M12, 5-pin)
Housing Size	40 x 50mm
Material - Housing	PBTP
Material - Window	Plexiglass
Operating Distance	30 - 40mm
Output	3 Outputs Programmable
Sensor Housing Size	4155
Temperature Range - Operating	-5° to +55°C

This document was generated on Aug 20, 2024