



**Part Number :** 1202540066

**Series Number :** 120254

**Product Category :** Inductive and Photoelectric Sensors

**Product Description :** Contrinex Photoelectric Sensor, 4mm Diameter Smooth Housing, Through-Beam (Emitter), 2m 3-wire PVC Cable, 35mm Housing Length

**Status :** Active

**Engineering Number :** LLR-D04MA-NMK-400


Documents & Resources

Specifications

Product Specification 1202540062-000.pdf

Product Environment Compliance

Compliance

GADSL/IMDS	Not Relevant
China RoHS	
EU ELV	Not Relevant
Low-Halogen Status	Not Reviewed per IEC 61249-2-21
REACH SVHC	Not Reviewed per D(2024)4144-DC (27 June 2024)
EU RoHS	Compliant per EU 2015/863

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

EU RoHS Certificate of Compliance

Part Details

General

Status	Active
Category	Inductive and Photoelectric Sensors
Series	120254
Description	Contrinex Photoelectric Sensor, 4mm Diameter Smooth Housing, Through-Beam (Emitter), 2m 3-wire PVC Cable, 35mm Housing Length
IP Rating	IP67
Operating Principle	Through-Beam (Emitter)
Product Family	Contrinex Inductive and Photoelectric Sensors
Product Name	Contrinex
Type	Photoelectric
UPC	191130067527

Electrical

Polarity	Emitter
----------	---------

Physical

Connection	Cable (PVC 2m, 3-wire)
Length	35mm
Material - Housing	Stainless Steel
Material - Window	Glass
Sensor Housing Size	4mm dia. (smooth)
Temperature Range - Operating	0° to +55°C