



Part Number : 1202540075

Series Number : 120254

Product Category : Inductive and Photoelectric Sensors

Product Description : Contrinex Photoelectric Sensor, 4mm Diameter Smooth Housing, Diffuse, 20mm Operating Distance, PNP, Light-ON, 3-pin M8 Connector, 45mm Housing Length

Status : Active

Engineering Number : LTR-D04MA-NMS-403


Documents & Resources

Specifications

Product Specification 1202540072-000.pdf

Product Environment Compliance

Compliance

GADSL/IMDS	Not Relevant
China RoHS	
EU ELV	Not Relevant
Low-Halogen Status	Not Reviewed per IEC 61249-2-21
REACH SVHC	Not Reviewed per D(2024)4144-DC (27 June 2024)
EU RoHS	Compliant per EU 2015/863

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

EU RoHS Certificate of Compliance

Part Details

General

Status	Active
Category	Inductive and Photoelectric Sensors
Series	120254
Description	Contrinex Photoelectric Sensor, M5 Housing, Diffuse, 50mm Operating Distance, PNP, Light-ON, 2m 3-wire PVC Cable, 35mm Housing Length
IP Rating	IP67
Operating Principle	Diffuse
Product Family	Contrinex Inductive and Photoelectric Sensors
Product Name	Contrinex
Type	Photoelectric
UPC	191130067930

Electrical

Polarity	PNP
Switching Frequency	≤ 250 Hz

Physical

Connection	Cable (PVC 2m, 3-wire)
Length	35mm
Material - Housing	Stainless Steel
Material - Window	Glass
Operating Distance	50mm
Output	Light-ON
Sensor Housing Size	M5
Temperature Range - Operating	0° to +55°C