# molex

Part Number: 2138651633

Product Description: NTC Ring Temperature Sensor-to-Micro-Lock Plus Cable Assembly, 75.00mm Length, 3982 Beta Value with 1% Tolerance, 10kOhm Resistance at 25°C with

1% Tolerance, Black

Series Number: 213865

Status: Active

**Product Category :** Power and Signal Cable Assemblies



#### **Documents & Resources**

#### **Drawings**

2138651633\_sd.pdf

### **Product Environment Compliance**

#### Compliance

| GADSL/IMDS         | Not Relevant                                      |
|--------------------|---|
| China RoHS         | <u> </u>  |
| EU ELV             | Not Relevant                                      |
| Low-Halogen Status | Not Low-Halogen per IEC 61249-2-<br>21            |
| REACH SVHC         | Contains Lead per D(2024)6225-DC<br>(07 Nov 2024) |
| EU RoHS            | Compliant with Exemption 15(a)<br>per EU 2015/863 |

#### Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

#### Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

# Part Details

## General

| Status                 | Active   |
|------------------------|--|
| Category               | Power and Signal Cable Assemblies  |
| Series                 | 213865   |
| Description            | NTC Ring Temperature Sensor-to-<br>Micro-Lock Plus Cable Assembly,<br>75.00mm Length, 3982 Beta Value<br>with 1% Tolerance, 10kOhm<br>Resistance at 25°C with 1%<br>Tolerance, Black |
| Application            | Temperature Sensing  |
| Assembly Configuration | Dual Ended Connectors  |
| Connector to Connector | Ring Term-to-Micro-Lock Plus   |
| Product Name           | NTC Temperature Sensor   |
| Туре                   | Discrete Wire Assembly   |
| UPC                    | 193264539482   |

## Electrical

| Beta Value (K)                | 3982            |
|-------------------------------|-----------------|
| Current - Maximum per Contact | 0.5A            |
| Resistance at 25°C (kohms)    | 10              |
| Resistance Tolerance (%)      | 1               |
| Voltage - Maximum             | 50V AC (RMS)/DC |

# Physical

| Cable Length                   | 75.00mm       |
|--------------------------------|---------------|
| Circuits (Loaded)              | 2             |
| Circuits (maximum)             | 2             |
| Color - Resin                  | Black         |
| Gender                         | Female-Female |
| Lock to Mating Part            | Yes           |
| Material - Metal               | Copper Alloy  |
| Material - Plating Mating      | Nickel        |
| Material - Plating Termination | Nickel, Tin   |

| Material - Resin            | PBT                  |
|-----------------------------|----------------------|
| Net Weight                  | 1.732/g              |
| Number of Rows              | 1                    |
| Overmolded                  | No                   |
| Packaging Type              | Bag                  |
| Pitch - Mating Interface    | 1.25mm               |
| Single Ended                | No                   |
| Stud Size                   | 6 (M3.5)             |
| Termination Interface Style | Crimp or Compression |
| Wire/Cable Type             | PTFE, UL 10344       |
| Wire Insulation Diameter    | 0.95mm               |
| Wire Size (AWG)             | 26                   |

## Mates With / Use With

# Mates with Part(s)

| Description   | Part Number   |
|---|---------------|
| 1.25mm Pitch Micro-Lock Plus<br>Vertical, Single Row, Surface Mount<br>Headers    | <u>505568</u> |
| 1.25mm Pitch Micro-Lock Plus<br>Right-Angle, Single Row, Surface<br>Mount Headers | <u>505567</u> |

This document was generated on Mar 13, 2025