

Part Number : 1202480009 Product Description : MPIS Micro-Change (M12) Passive Junction Box, Top-Mount, 4 Ports, LED for NPN Sensor, WSOR Cable, 15.0m Length Series Number : 120248 Status : Active Product Category : Passive Distribution Boxes Engineering Number : BTB400N-FBW-15



Documents & Resources

Drawings 1202480009_sd.pdf

Product Environment Compliance

Compliance

| GADSL/IMDS | Not Relevant |
|--------------------|--|
| China RoHS | @ |
| EU ELV | Not Relevant |
| Low-Halogen Status | Not Low-Halogen per IEC 61249-2- 21 |
| REACH SVHC | Contains Lead; Triphenyl- phosphate per D(2024)6225-DC (07 Nov 2024) |
| EU RoHS | Compliant with Exemption 6(c) per EU 2015/863 |

Multiple Part Product Compliance Statements

- Eu RoHS

- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration

- IEC-62474

- chemSHERPA (xml)

EU RoHS Certificate of Compliance

Part Details

General

| Status | Active |
|--------------|---|
| Category | Passive Distribution Boxes |
| Series | 120248 |
| Description | MPIS Micro-Change (M12) Passive Junction Box, Top-Mount, 4 Ports, LED for NPN Sensor, WSOR Cable, 15.0m Length |
| IP Rating | IP67 |
| Product Name | MPIS |
| UPC | 889056329613 |

Agency

| UL | E152210 |
|----|---------|
| | |

Electrical

| Current - Maximum per Contact | 12.0A per module, 4.0A per port |
|-------------------------------|---------------------------------|
| Functional Wiring | NPN |
| Voltage - Maximum | 10-30V DC |
| Wiring Configuration | Single I/O per Port |

Physical

| Bus I/O | N/A |
|-----------------------------|-------------|
| Cable Connector Orientation | Straight |
| Cable Length | 15.0m |
| Home Run Cable Length | 15.0m |
| Home Run Connector | N/A |
| Home Run Interface | Pigtail |
| Keyway | A-Coded |
| LED Indicator | NPN Sensors |
| Material - Cable Jacket | TPU |

| Material - Housing | PBT |
|-------------------------------|----------------|
| Material - Metal | Copper Alloy |
| Material - Plating Mating | Gold |
| Net Weight | 1452.520/g |
| Orientation | Top-Mount |
| Poles | 4 |
| Poles (wired) | 4 |
| Ports | 4 |
| Temperature Range - Operating | -25°C to +85°C |
| Wire/Cable Type | WSOR |

This document was generated on Jan 11, 2025