

Home > Products > LED Drivers > General Driver > Outdoor use - H series > MU035H

MU035H



Products

Motor and Drives

Stepper Motors

Servo Mbtors

BLDC Motors

LED Drivers

> General Driver

> Outdoor use - CP series

> Outdoor use - C series

> Outdoor use - H series

> PU012H

> PU025H

> PU040H

> MU035H

> MU050H

> MU060H

> MU075H

> MU100H

> MU120H

> MU150H

> MU200H

> Outdoor use - half-potted series

> Outdoor use - 277-480VAC input series

> Outdoor use - other series

> Outdoor use - Aseries

> Accessories-Configurator

> Intelligent Driver

Intelligent lighting control system

Switching Power Supplies

Assembly Technology

MU035H

Basic parameters

Specifications

Certificates



.....
T:(CN) +86-021-52634688
F:(CN) +86-021-52634098
T:(US) +1-630-833-5940
T:(EU) +39-039-62-60-521
T:(SE Asia) +65-6634-1198
T:(JP) +81-045-475-5788
mail: info@moons.com.cn
.....

▶ Contact Us

- Input voltage range: 90-305 VAC
- High efficiency: 90% typical
- Active PFC: 0.99 typical
- High surge immunity
- Low THD 10% Typ.
- IP67 compliant
- Protections: OVP, OTP, SCP
- Compliance to worldwide safety regulations for lighting
- Suitable for dry/damp locations
- CUL / CCC(in process)
- 5-year warranty



For Model Numbering System for LED Drivers

constant current

model no.	output current (ma)	output voltage (vdc)	efficiency 110vac (typical)	efficiency 220vac (typical)
MU035H035AQ	350	50-100	90%	91%
MU035H045AQ	450	39-78	89%	90%
MU035H053AQ	530	33-66	88%	89%
MU035H070AQ	700	25-50	87%	88%
MU035H085AQ	850	21-41	87%	88%
MU035H105AQ	1050	16-33	87%	88%
MU035H120AQ	1200	15-29	87%	88%
MU035H140AQ	1400	13-25	86%	87%
MU035H175AQ	1750	10-20	86%	87%
MU050H210AQ	2100	9-17	85%	86%

0-10V dimming

model no.	output current (ma)	output voltage (vdc)	efficiency 110vac (typical)	efficiency 220vac (typical)
MU035H035AQ_0-10V	350	50-100	90%	91%
MU035H045AQ_0-10V	450	39-78	89%	90%
MU035H053AQ_0-10V	530	33-66	88%	89%
MU035H070AQ_0-10V	700	25-50	87%	88%
MU035H085AQ_0-10V	850	21-41	87%	88%
MU035H105AQ_0-10V	1050	16-33	87%	88%
MU035H120AQ_0-10V	1200	15-29	87%	88%
MU035H140AQ_0-10V	1400	13-25	86%	87%
MU035H175AQ_0-10V	1750	10-20	86%	87%
MU050H210AQ_0-10V	2100	9-17	85%	86%

clock dimming

model no.	output current (ma)	output voltage (vdc)	efficiency 110vac (typical)	efficiency 220vac (typical)
MU035H035AQ_CLKS	350	50-100	90%	91%
MU035H045AQ_CLKS	450	39-78	89%	90%
MU035H053AQ_CLKS	530	33-66	88%	89%
MU035H070AQ_CLKS	700	25-50	87%	88%
MU035H085AQ_CLKS	850	21-41	87%	88%
MU035H105AQ_CLKS	1050	16-33	87%	88%
MU035H120AQ_CLKS	1200	15-29	87%	88%
MU035H140AQ_CLKS	1400	13-25	86%	87%
MU035H175AQ_CLKS	1750	10-20	86%	87%
MU050H210AQ_CLKS	2100	9-17	85%	86%

ADJ

model no.	output current (ma)	output voltage (vdc)	efficiency 110vac (typical)	efficiency 220vac (typical)
MU035H035AQ_ADJ	350	50-100	90%	91%
MU035H045AQ_ADJ	450	39-78	89%	90%
MU035H053AQ_ADJ	530	33-66	88%	89%
MU035H070AQ_ADJ	700	25-50	87%	88%
MU035H085AQ_ADJ	850	21-41	87%	88%
MU035H105AQ_ADJ	1050	16-33	87%	88%
MU035H120AQ_ADJ	1200	15-29	87%	88%
MU035H140AQ_ADJ	1400	13-25	86%	87%
MU035H175AQ_ADJ	1750	10-20	86%	87%
MU050H210AQ_ADJ	2100	9-17	85%	86%

