


DC/DC Converter

K78Lxx-1000R2 Series

MORNSUN®

Wide input voltage , non-isolated & regulated
single output



Patent Protection RoHS

FEATURES

- Efficiency up to 91%
- Low ripple & noise
- Without heatsink
- Short circuit protection and overheat protection
- Pin-out compatible with LM78XX series
- Operating temperature range: -40°C to +85°C
- Subminiature SIP package, meeting requirements of UL94-V0
- Low cost
- Industry standard pin-out

K78Lxx-1000R2 series are high efficiency switching regulators and ideal substitutes of LM78XX series three-terminal linear regulators. The product is featured with high efficiency, low loss, low radiation and no heat sink requirement. They are widely used in industrial control, instrumentation, and electric power applications.

Selection Guide

Part No.	Input Voltage (VDC)	Output		Efficiency (%/Typ.) (Min. Vin)/ (Max. Vin)	Max. Capacitive Load(μF)
	Nominal (Range)	Output Voltage (VDC)	Output Current (mA)		
K78L05-1000R2	12 (6.5-18)	5.0	1000	91/88	1000

Input Specifications

Item	Operating Conditions	Min.	Typ.	Max.	Unit
No-load Power Consumption	Input voltage range	--	--	0.27	W
Reverse Polarity Input		Forbidden			
Input Filter		Capacitor filter			

Output Specifications

Item	Operating Conditions	Min.	Typ.	Max.	Unit
Output Voltage Accuracy	100% load, input voltage range	--	±2	±3	%
Line Regulation	Input voltage range	--	±0.4	±0.75	
Load Regulation	10%-100% load	--	±0.5	±1.0	
Ripple & Noise*	20MHz bandwidth (refer to Fig. 2)	--	20	35	mVp-p
Temperature Drift Coefficient	-40°C to +85°C	--	--	±0.025	%/°C
Over temperature Protection	IC built-in	--	--	160	°C
Output short circuit protection		Continuous, self-recovery			
Transient response deviation	Nominal input, 25% load step change	--	55	250	mV
Transient recovery time		--	0.5	3	ms
Thermal impedance		--	85	--	°C / W

Note: * Ripple and noise tested with "parallel cable" method, please see *DC-DC Converter Application Notes* for specific operation methods.

General Specifications

Item	Operating Condition	Min.	Typ.	Max.	Unit
Operating Temperature	Derating if the temperature ≥55 °C (see Fig. 1)	-40	--	85	°C
Storage Temperature		-55	--	125	
Max. Operating Temperature for casing	Within the operating temperature curve	--	--	100	
Pin Welding Resistance Temperature	Welding spot is 1.5mm away from the casing, 10 seconds	--	--	300	
Storage Humidity	Non-condensing	--	--	95	%RH
Switching Frequency	100% load, input voltage range	350	400	450	KHz
MTBF	MIL-HDBK-217F@25°C	1000	--	--	K hours

MORNSUN®

MORNSUN GUANGZHOU SCIENCE & TECHNOLOGY CO.,LTD.

2015.12.21-A/2

Page 1 of 4

MORNSUN Guangzhou Science & Technology Co., Ltd. reserves the copyright and right of final interpretation

Physical Specifications

Casing Material	Black flame-retardant and heat-resistant plastic (UL94-V0)
Package Dimensions	11.60*7.55*10.16 mm
Weight	2.00g (Typ.)
Cooling Method	Free air convection

EMC Specifications

EMI	Conducted Disturbance	CISPR22/EN55022	CLASS B	(see Fig. 4-② for recommended circuit)
	Radiated Emission	CISPR22/EN55022	CLASS B	(see Fig. 4-② for recommended circuit)
EMS	Electrostatic Discharge	IEC/EN 61000-4-2	Contact $\pm 4\text{KV}$	perf. Criteria B
	Radiation Immunity	IEC/EN 61000-4-3	10V/m	perf. Criteria A
	EFT	IEC/EN 61000-4-4	$\pm 1\text{KV}$	(see Fig. 4-① for recommended circuit) perf. Criteria B
	Surge Immunity	IEC/EN 61000-4-5	$\pm 1\text{KV}$	(see Fig. 4-① for recommended circuit) perf. Criteria B
	Conducted Disturbance Immunity	IEC/EN 61000-4-6	3Vr.m.s	perf. Criteria A
	Voltage dip, drop and short interruption	IEC/EN 61000-4-29	0%-70%	perf. Criteria B

Product Characteristic Curve









Fig. 1



1. Typical application circuit



③ No parallel connection and plug and play.

Fig. 3

Fig. 4 Recommended EMC circuit





Fig.5 Recommended EMC circuit-PCB layout

FUSE	MOV	LDM1	C0	C1/C2	C3	LDM2
Selected based on the actual input current from the customer	S10K35	82μH	680μF /50V	Refer to Fig.2	4.7μF /50V	12μH

Note: Part ① in the Fig. 4 is for EMS test, part ② is for EMI filtering; parts ① and ② can be added based on actual requirement.


3. For more information please find the application notes on www.mornsun-power.com

Dimensions and Recommended Layout



Note:
Unit :mm[inch]
Pin section tolerances:±0.10[±0.004]
General tolerances:±0.25[±0.010]

THIRD ANGLE PROJECTION



Ø1.00 [Ø0.039]
Note : Grid 2.54*2.54mm

Pin-Out	
Pin	Positive Output
1	Vin
2	GND
3	+Vo

Notes:

1. Packing Information please refer to 'Product Packing Information'. Packing bag number: 58200003;
2. The max. capacitive load should be tested within the input voltage range and under full load conditions;
3. Unless otherwise specified, data in this datasheet should be tested under the conditions of Ta=25°C, humidity<75% when inputting nominal voltage and outputting rated load;
4. All index testing methods in this datasheet are based on our Company's corporate standards;
5. The performance indexes of the product models listed in this manual are as above, but some indexes of non-standard model products will exceed the above-mentioned requirements, and please directly contact with our technician for specific information;
6. We can provide product customization service;
7. Specifications of this product are subject to changes without prior notice.

Mornsun Guangzhou Science & Technology Co., Ltd.

Address: No. 5, Kehui St. 1, Kehui Development Center, Science Ave., Guangzhou Science City, Luogang District, Guangzhou, P. R. China
Tel: 86-20-38601850-8801 Fax: 86-20-38601272 E-mail: info@mornsun.cn