

R6-3W Series



3W 2:1 Regulated Single & Dual output

Features

- Wide 2:1 Input Range
- Full SMD Technology
- 1500 VDC Isolation, Up to 3500 VDC
- Continuous Short Circuit Protection
- Efficiency up to 80%
- -40 ~ 85°C Operating Temperature
- Plastic Case Standard, Optional Metal Case





The R6 series is a family of cost effective 3W single & dual output DC-DC converters. These converters combine Plastic case in a 24-pin DIL package with high performance features such as 1500 VDC ~ 3500VDC input/output isolation voltage, continuous short circuit protection with automatic restart and tight line / load regulation. Devices are encapsulated using flame retardant resin. Input voltages of 5, 12, 24 and 48 with output voltage of 5, 9, 12, 15, 24, ± 5 , ± 9 , ± 12 , ± 15 and ± 24 Vdc. High performance features include high efficiency operation up to 80% and output voltage accuracy of $\pm 1\%$ maximum.

All specifications typical at $T_a=25^\circ\text{C}$, nominal input voltage and full load unless otherwise specified

OUTPUT SPECIFICATIONS		PHYSICAL SPECIFICATIONS	
Voltage accuracy	$\pm 1\%$	Case Material	Non-conductive Black Plastic(UL94V-0 rated)
Line regulation	$\pm 0.5\%$		Nickel-coated Copper
Load regulation	$\pm 0.5\%$	Base Material	Non-conductive Black Plastic(UL94V-0 rated)
Ripple & noise(20 MHz bandwidth)(1)	60mV pk-pk	Pin Material	$\varnothing 0.5\text{mm}$ Brass Solder-coated
Short circuit protection	Continuous	Potting Material	Epoxy (UL94V-0 rated)
Temperature coefficient	$\pm 0.02\%/^\circ\text{C}$	Weight	12.5g(Plastic Case)/15.0g(Metal Case)
Capacitor load(2)	See table	Dimensions	1.25"x0.8"x0.4"
INPUT SPECIFICATIONS		ABSOLUTE MAXIMUM RATINGS(4)	
Voltage Range	See table	These are stress ratings. Exposure of devices to any of these conditions may adversely affect long-term reliability.	
Max. Input Current	See table	Input Voltage(100mS)	
No-Load Input Current	See table	5 Modes	-0.7~15 Vdc
Input Filter	PI Type	12 Modes	-0.7~24 Vdc
Input Reflected Ripple Current(3)	35mA pk-pk	24 Modes	-0.7~40 Vdc
		48 Modes	-0.7~80 Vdc
GENERAL SPECIFICATIONS		Soldering Temperature	260°C
Efficiency	See table, typ	(1.5mm from case 10sec.)	
I/O Isolation Voltage(3 sec)		EMC SPECIFICATIONS	
Input/Output	1500~3500Vdc	Radiated Emissions	EN55022 CLASS A
Metal Case/Input & Output	1000Vdc	Conducted Emissions (7)	EN55022 CLASS A
I/O Isolation Capacitance	60 pF Typ.	ESD	IEC 61000-4-2 Perf. Criteria B
I/O Isolation Resistance	1000M Ohm	RS	IEC 61000-4-3 Perf. Criteria A
Switching Frequency	100~400kHz	EFT (8)	IEC 61000-4-4 Perf. Criteria B
Humidity	95% rel H	Surge (8)	IEC 61000-4-5 Perf. Criteria B
Reliability Calculated MTBF(MIL-HDBK-217 F)	>2.199 Mhrs	CS	IEC 61000-4-6 Perf. Criteria A
Safety Standard : (designed to meet)	IEC 60950-1	PFMF	IEC 61000-4-8 Perf. Criteria A
ENVIRONMENT SPECIFICATIONS			
Operating Temperature	-40°C~85°C(See Derating Curve)		
Maximum Case Temperature	100°C		
Storage Temperature	-40°C~125°C		
Cooling	Nature Convection		

R6 - 3W 2:1 Regulated Single & Dual output

PART NUMBER STRUCTURE



MODEL SELECTION GUIDE

MODEL NUMBER	INPUT Voltage Range (Vdc)	INPUT Current		OUTPUT Voltage (Vdc)	OUTPUT Current		EFFICIENCY @FL(%)	Capacitor Load(uF)
		No-Load (mA)	Full Load (mA)		Min. load (mA)	Full load (mA)		
R6-0505S3	4.5-9	40	857	5	150	600	70	2200
R6-0509S3	4.5-9	40	833	9	83.3	333	72	470
R6-0512S3	4.5-9	40	810	12	62.5	250	74	470
R6-0515S3	4.5-9	40	810	15	50	200	74	470
R6-0524S3	4.5-9	40	857	24	31.3	125	70	220
R6-0505D3	4.5-9	40	869	±5	±75	±300	69	±1000
R6-0509D3	4.5-9	40	857	±9	±41.8	±167	70	±220
R6-0512D3	4.5-9	40	833	±12	±31.3	±125	72	±220
R6-0515D3	4.5-9	40	810	±15	±25	±100	74	±220
R6-0524D3	4.5-9	40	857	±24	±15.8	±63	70	±100
R6-1205S3	9-18	20	328	5	150	600	76	2200
R6-1209S3	9-18	20	324	9	83.3	333	77	470
R6-1212S3	9-18	20	316	12	62.5	250	79	470
R6-1215S3	9-18	20	316	15	50	200	79	470
R6-1224S3	9-18	20	316	24	31.3	125	79	220
R6-1205D3	9-18	20	324	±5	±75	±300	77	±1000
R6-1209D3	9-18	20	320	±9	±41.8	±167	78	±220
R6-1212D3	9-18	20	320	±12	±31.3	±125	78	±220
R6-1215D3	9-18	20	320	±15	±25	±100	78	±220
R6-1224D3	9-18	20	320	±24	±15.8	±63	78	±100
R6-2405S3	18-36	12	156	5	150	600	80	2200
R6-2409S3	18-36	12	156	9	83.3	333	80	470
R6-2412S3	18-36	12	152	12	62.5	250	82	470
R6-2415S3	18-36	12	152	15	50	200	82	470
R6-2424S3	18-36	12	156	24	31.3	125	80	220
R6-2405D3	18-36	12	160	±5	±75	±300	78	±1000
R6-2409D3	18-36	12	158	±9	±41.8	±167	79	±220
R6-2412D3	18-36	12	156	±12	±31.3	±125	80	±220
R6-2415D3	18-36	12	156	±15	±25	±100	80	±220
R6-2424D3	18-36	12	156	±24	±15.8	±63	80	±100

Suffix "H" means 3.5KVdc isolation

Suffix "M" means Metal Case instead of standard Plastic case

R6 - 3W 2:1 Regulated Single & Dual output

MODEL NUMBER	INPUT Voltage Range (Vdc)	INPUT Current		OUTPUT Voltage (Vdc)	OUTPUT Current		EFFICIENCY @FL(%)	Capacitor Load(uF)
		No-Load (mA)	Full Load (mA)		Min. load (mA)	Full load (mA)		
R6-4805S3	36-72	8	81	5	150	600	77	2200
R6-4809S3	36-72	8	80	9	83.3	333	78	470
R6-4812S3	36-72	8	78	12	62.5	250	80	470
R6-4815S3	36-72	8	78	15	50	200	80	470
R6-4824S3	36-72	8	78	24	31.3	125	80	220
R6-4805D3	36-72	8	80	±5	±75	±300	78	±1000
R6-4809D3	36-72	8	79	±9	±41.8	±167	79	±220
R6-4812D3	36-72	8	78	±12	±31.3	±125	80	±220
R6-4815D3	36-72	8	78	±15	±25	±100	80	±220
R6-4824D3	36-72	8	78	±24	±15.8	±63	80	±100


Suffix "H" means 3.5KVdc isolation

Suffix "M" means Metal Case instead of standard Plastic case

TEST CONFIGURATIONS

EMI Filter

Input filter components (C1, L) are used to help meet conducted emissions requirement for the module. These components should be mounted as close as possible to the module; and all leads should be minimized to decrease radiated noise.




	C1	L	C2
R6-05XXXXX	220uF/100V	12uH	
R6-12XXXXX	220uF/100V	12uH	
R6-24XXXXX	220uF/100V	12uH	MLCC 471K
R6-48XXXXX	220uF/100V	12uH	MLCC 471K

NOTE

1. Typical value at nominal input voltage and full load.
2. Test by nominal input voltage and constant resistor load.
3. Measured Input reflected ripple current with a simulated source inductance of 12uH.
4. Exceeding the absolute ratings of the unit could cause damage. It is not allowed for continuous operating.
5. Operation under no-load conditions will not damage these devices, however they may not meet all listed specifications.
6. It's necessary to add minimum capacitor in output for some models, please check single model datasheet for detail value.
7. Input filter components are required to help meet conducted emission class A, which application refers to the EMI Filter of design & feature configuration.
8. An external filter capacitor is required if the module has to meet EN61000-4-4 and EN61000-4-5.
The filter capacitor Motien suggests: Nippon - chemi - con KY series, 220uF/100V.

MECHANICAL SPECIFICATIONS FOR HIGH ISOLATION MODEL




Notes: All dimensions are typical in millimeters (inches).
 1. Pin diameter: 0.5 ± 0.05 (0.02 ± 0.002)
 2. Pin pitch tolerance: ± 0.35 (± 0.014)
 3. Case Tolerance: ± 0.5 (± 0.02)

PIN CONNECTIONS

PIN NUMBER	SINGLE	DUAL	SINGLE-H	DUAL-H
1	+V Input	+V Input	N.P.	N.P.
2	N.C.	-V Output	-V Input	-V Input
3	N.C.	Common	-V Input	-V Input
9	N.P.	N.P.	N.P.	Common
10	-V Output	Common	N.P.	N.P.
11	+V Output	+V Output	N.C.	-V Output
12	-V Input	-V Input	N.P.	N.P.
13	-V Input	-V Input	N.P.	N.P.
14	+V Output	+V Output	+V Output	+V Output
15	-V Output	Common	N.P.	N.P.
16	N.P.	N.P.	-V Output	Common
22	N.C.	Common	+V Input	+V Input
23	N.C.	-V Output	+V Input	+V Input
24	+V Input	+V Input	N.P.	N.P.

MECHANICAL SPECIFICATIONS



Notes: All dimensions are typical in millimeters (inches).
 1. Pin diameter: 0.5 ± 0.05 (0.02 ± 0.002)
 2. Pin pitch tolerance: ± 0.35 (± 0.014)
 3. Case Tolerance: ± 0.5 (± 0.02)
 4. Stand-off tolerance: ± 0.1 (± 0.004)

PIN CONNECTIONS

PIN NUMBER	SINGLE	DUAL	SINGLE-H	DUAL-H
1	+V Input	+V Input	N.P.	N.P.
2	N.C.	-V Output	-V Input	-V Input
3	N.C.	Common	-V Input	-V Input
9	N.P.	N.P.	N.P.	Common
10	-V Output	Common	N.P.	N.P.
11	+V Output	+V Output	N.C.	-V Output
12	-V Input	-V Input	N.P.	N.P.
13	-V Input	-V Input	N.P.	N.P.
14	+V Output	+V Output	+V Output	+V Output
15	-V Output	Common	N.P.	N.P.
16	N.P.	N.P.	-V Output	Common
22	N.C.	Common	+V Input	+V Input
23	N.C.	-V Output	+V Input	+V Input
24	+V Input	+V Input	N.P.	N.P.