

V6-6W Series

6W 2:1 Regulated Single & Dual output

Features

- Wide 2:1 Input Range
- Full SMD Technology
- 1500 VDC Isolation, Up to 3500 VDC
- Continuous Short Circuit Protection
- Efficiency up to 83%
- -40 ~ 85°C Operation Temperature Range
- Metal Case Standard, Optional Plastic Case



The V6 series is a family of cost effective 6W single & dual output DC-DC converters. These converters are consisted with Nickle-coated copper in a 24-pin DIL package with high performance features such as 1500 VDC ~ 3500VDC input/output isolation voltage, continuous short circuit protection with automatic restart and tight line / load regulation. Devices are encapsulated using flame retardant resin. Input voltages of 12, 24 and 48 with output voltage of 3.3, 5, 9, 12, 15, 24, ± 3.3 , ± 5 , ± 9 , ± 12 , ± 15 and ± 24 Vdc. High performance features include high efficiency operation up to 83% and output voltage accuracy of $\pm 1\%$ maximum.



All specifications typical at $T_a = 25^\circ\text{C}$, nominal input voltage and full load unless otherwise specified

OUTPUT SPECIFICATIONS		PHYSICAL SPECIFICATIONS	
Voltage accuracy	$\pm 1\%$	Case Material	Nickel-coated Copper
Line regulation	$\pm 0.5\%$		Non-conductive Black Plastic (UL94V-0 rated)
Load regulation	$\pm 0.5\%$	Base Material	Non-conductive Black Plastic (UL94V-0 rated)
	(Output 3.3V / $\pm 3.3\text{V}$ Model) $\pm 1.5\%$	Pin Material	$\varnothing 0.5\text{mm}$ Brass Solder-coated
Ripple & noise (20 MHz bandwidth)(1)	60mV pk-pk	Potting Material	Epoxy (UL94V-0 rated)
Short circuit protection	Indefinite (Automatic Recovery)	Weight	17.0g (Metal Case) / 13.5g (Plastic Case)
Temperature coefficient	$\pm 0.02\% / ^\circ\text{C}$	Dimensions	1.25" x 0.8" x 0.4"
Capacitor load(2)	See table		
INPUT SPECIFICATIONS		ENVIRONMENT SPECIFICATIONS	
Voltage Range	See table	Operating Temperature	$-40^\circ\text{C} \sim 85^\circ\text{C}$ (See Derating Curve)
Max. Input Current	See table	Maximum Case Temperature	100°C
No-Load Input Current	See table	Storage Temperature	$-40^\circ\text{C} \sim 125^\circ\text{C}$
Input Filter	PI Type	Cooling	Nature Convection
Input Reflected Ripple Current(3)	35mA pk-pk		
GENERAL SPECIFICATIONS		ABSOLUTE MAXIMUM RATINGS(4)	
Efficiency	See table, typ	These are stress ratings. Exposure of devices to any of these conditions may adversely affect long-term reliability.	
I/O Isolation Voltage(3 sec)		Input Voltage(100mS)	
Input/Output	1500~3500Vdc	12 Modes	-0.7~24 Vdc
Metal Case/Input & Output	1000Vdc	24 Modes	-0.7~40 Vdc
I/O Isolation Capacitance	470 pF Typ.	48 Modes	-0.7~80 Vdc
I/O Isolation Resistance	1000M Ohm	Lead Soldering Temperature	260°C
Switching Frequency	Typical 266kHz	(1.5mm from case 10sec.)	
Humidity	95% rel H		
Reliability Calculated MTBF(MIL-HDBK-217 F)	>1.121 Mhrs		
Safety Standard : (designed to meet)	IEC 60950-1:2001		

The information and specifications contained in this data sheet are believed to be correct at time of publication. However, MOTIEN Technologies accepts no responsibility for consequences arising from printing errors or inaccuracies. Specifications are subject to change without notice. No rights under any patent accompany the sale of any such product(s) or information contained herein.

V6 - 6W 2:1 Regulated Single & Dual output

PART NUMBER STRUCTURE



MODEL SELECTION GUIDE

MODEL NUMBER	INPUT Voltage Range (Vdc)	INPUT Current		OUTPUT Voltage (Vdc)	OUTPUT Current		EFFICIENCY @FL(%)	Capacitor Load(uF)
		No-Load (mA)	Full Load (mA)		Min. load (mA)	Full load (mA)		
V6-123R3S6	9-18	30	527	3.3	0	1400	73	1000
V6-1205S6	9-18	30	649	5	0	1200	77	1000
V6-1209S6	9-18	30	641	9	0	666	78	680
V6-1212S6	9-18	30	617	12	0	500	81	330
V6-1215S6	9-18	30	625	15	0	400	80	220
V6-1224S6	9-18	30	625	24	0	250	80	68
V6-123R3D6	9-18	30	527	±3.3	0	±909	73	±680
V6-1205D6	9-18	30	649	±5	0	±600	77	±330
V6-1209D6	9-18	30	625	±9	0	±333	80	±220
V6-1212D6	9-18	30	625	±12	0	±250	80	±100
V6-1215D6	9-18	30	632	±15	0	±200	79	±47
V6-1224D6	9-18	30	625	±24	0	±125	80	±33
V6-243R3S6	18-36	20	256	3.3	0	1400	75	1000
V6-2405S6	18-36	20	313	5	0	1200	80	1000
V6-2409S6	18-36	20	304	9	0	666	82	680
V6-2412S6	18-36	20	313	12	0	500	80	330
V6-2415S6	18-36	20	304	15	0	400	82	220
V6-2424S6	18-36	20	305	24	0	250	82	68
V6-243R3D6	18-36	20	333	±3.3	0	±909	75	±680
V6-2405D6	18-36	20	321	±5	0	±600	78	±330
V6-2409D6	18-36	20	301	±9	0	±333	83	±220
V6-2412D6	18-36	20	312	±12	0	±250	80	±100
V6-2415D6	18-36	20	312	±15	0	±200	80	±47
V6-2424D6	18-36	20	312	±24	0	±125	80	±33
V6-483R3S6	36-72	12	128	3.3	0	1400	75	1000
V6-4805S6	36-72	12	156	5	0	1200	80	1000
V6-4809S6	36-72	12	152	9	0	666	82	680
V6-4812S6	36-72	12	156	12	0	500	80	330
V6-4815S6	36-72	12	151	15	0	400	83	220
V6-4824S6	36-72	12	151	24	0	250	83	68

Suffix "H" means 3.5KVdc isolation

Suffix "P" means Plastic case instead of standard Metal Case

V6 - 6W 2:1 Regulated Single & Dual output


MODEL NUMBER	INPUT Voltage Range (Vdc)	INPUT Current		OUTPUT Voltage (Vdc)	OUTPUT Current		EFFICIENCY @FL(%)	Capacitor Load(uF)
		No-Load (mA)	Full Load (mA)		Min. load (mA)	Full load (mA)		
V6-483R3D6	36-72	12	171	±3.3	0	±909	73	±680
V6-4805D6	36-72	12	158	±5	0	±600	79	±330
V6-4809D6	36-72	12	158	±9	0	±333	79	±220
V6-4812D6	36-72	12	156	±12	0	±250	80	±100
V6-4815D6	36-72	12	156	±15	0	±200	80	±47
V6-4824D6	36-72	12	156	±24	0	±125	80	±33

Suffix "H" means 3.5KVdc isolation


Suffix "P" means Plastic case instead of standard Metal Case

NOTE


1. Typical value at nominal input voltage and full load.
2. Test by nominal input voltage and constant resistor load.
3. Measured Input reflected ripple current with a simulated source inductance of 12uH.
4. Exceeding the absolute ratings of the unit could cause damage. It is not allowed for continuous operating.



12 Models




24 Models



48 Models


V6 - 6W 2:1 Regulated Single & Dual output

MECHANICAL SPECIFICATIONS



PIN CONNECTIONS				
PIN NUMBER	SINGLE	DUAL	SINGLE-H	DUAL-H
1	+V Input	+V Input	N.P.	N.P.
2	N.C.	-V Output	-V Input	-V Input
3	N.C.	Common	-V Input	-V Input
9	N.P.	N.P.	N.C.	Common
10	-V Output	Common	N.P.	N.P.
11	+V Output	+V Output	N.C.	-V Output
12	-V Input	-V Input	N.P.	N.P.
13	-V Input	-V Input	N.P.	N.P.
14	+V Output	+V Output	+V Output	+V Output
15	-V Output	Common	N.P.	N.P.
16	N.P.	N.P.	-V Output	Common
22	N.C.	Common	+V Input	+V Input
23	N.C.	-V Output	+V Input	+V Input
24	+V Input	+V Input	N.P.	N.P.

MECHANICAL SPECIFICATIONS



PIN CONNECTIONS				
PIN NUMBER	SINGLE	DUAL	SINGLE-H	DUAL-H
1	+V Input	+V Input	N.P.	N.P.
2	N.C.	-V Output	-V Input	-V Input
3	N.C.	Common	-V Input	-V Input
9	N.P.	N.P.	N.C.	Common
10	-V Output	Common	N.P.	N.P.
11	+V Output	+V Output	N.C.	-V Output
12	-V Input	-V Input	N.P.	N.P.
13	-V Input	-V Input	N.P.	N.P.
14	+V Output	+V Output	+V Output	+V Output
15	-V Output	Common	N.P.	N.P.
16	N.P.	N.P.	-V Output	Common
22	N.C.	Common	+V Input	+V Input
23	N.C.	-V Output	+V Input	+V Input
24	+V Input	+V Input	N.P.	N.P.