

V6-3W Series

3W 2:1 Regulated Single & Dual output

Features

- Wide 2:1 Input Range
- Full SMD Technology
- 1500 VDC Isolation, Up to 3500 VDC
- Continuous Short Circuit Protection
- Efficiency up to 82%
- -40 ~ 85°C Operation Temperature Range
- Metal Case Standard, Optional Plastic Case





The V6 series is a family of cost effective 3W single & dual output DC-DC converters. These converters are consisted with Nickle-coated copper in a 24-pin DIL package with high performance features such as 1500 VDC ~ 3500VDC input/output isolation voltage, continuous short circuit protection with automatic restart and tight line / load regulation. Devices are encapsulated using flame retardant resin. Input voltages of 12, 24 and 48 with output voltage of 3.3, 5, 9, 12, 15, 24, ± 3.3 , ± 5 , ± 9 , ± 12 , ± 15 and ± 24 Vdc. High performance features include high efficiency operation up to 82% and output voltage accuracy of $\pm 1\%$ maximum.

All specifications typical at $T_a = 25^\circ\text{C}$, nominal input voltage and full load unless otherwise specified

OUTPUT SPECIFICATIONS		PHYSICAL SPECIFICATIONS	
Voltage accuracy	$\pm 1\%$	Case Material	Nickel-coated Copper
Line regulation	$\pm 0.5\%$		Non-conductive Black Plastic (UL94V-0 rated)
Load regulation	$\pm 0.5\%$	Base Material	Non-conductive Black Plastic (UL94V-0 rated)
	(Output 3.3V / $\pm 3.3\text{V}$ Model) $\pm 1.5\%$	Pin Material	$\varnothing 0.5\text{mm}$ Brass Solder-coated
Ripple & noise (20 MHz bandwidth)(1)	60mV pk-pk	Potting Material	Epoxy (UL94V-0 rated)
Short circuit protection	Indefinite (Automatic Recovery)	Weight	17.0g (Metal Case) / 13.5g (Plastic Case)
Temperature coefficient	$\pm 0.02\%/^\circ\text{C}$	Dimensions	1.25" x 0.8" x 0.4"
Capacitor load(2)	See table		
INPUT SPECIFICATIONS		ENVIRONMENT SPECIFICATIONS	
Voltage Range	See table	Operating Temperature	$-40^\circ\text{C} \sim 85^\circ\text{C}$ (See Derating Curve)
Max. Input Current	See table	Maximum Case Temperature	100°C
No-Load Input Current	See table	Storage Temperature	$-40^\circ\text{C} \sim 125^\circ\text{C}$
Input Filter	PI Type	Cooling	Nature Convection
Input Reflected Ripple Current(3)	35mA pk-pk		
GENERAL SPECIFICATIONS		ABSOLUTE MAXIMUM RATINGS(4)	
Efficiency	See table, typ	These are stress ratings. Exposure of devices to any of these conditions may adversely affect long-term reliability.	
I/O Isolation Voltage(3 sec)		Input Voltage(100ms)	
Input/Output	1500~3500Vdc	12 Modes	-0.7~24 Vdc
Metal Case/Input & Output	1000Vdc	24 Modes	-0.7~40 Vdc
I/O Isolation Capacitance	470 pF Typ.	48 Modes	-0.7~80 Vdc
I/O Isolation Resistance	1000M Ohm	Soldering Temperature	260°C
Switching Frequency	Typical 266kHz	(1.5mm from case 10sec.)	
Humidity	95% rel H		
Reliability Calculated MTBF(MIL-HDBK-217 F)	>1.121 Mhrs		
Safety Standard : (designed to meet)	IEC 60950-1		

V6 - 3W 2:1 Regulated Single & Dual output

PART NUMBER STRUCTURE



MODEL SELECTION GUIDE

MODEL NUMBER	INPUT Voltage Range (Vdc)	INPUT Current		OUTPUT Voltage (Vdc)	OUTPUT Current		EFFICIENCY @FL(%)	Capacitor Load(uF)
		No-Load (mA)	Full Load (mA)		Min. load (mA)	Full load (mA)		
V6-123R3S3	9-18	22	343	3.3	0	900	72	470
V6-1205S3	9-18	22	328	5	0	600	76	470
V6-1209S3	9-18	22	320	9	0	333	78	68
V6-1212S3	9-18	22	312	12	0	250	80	47
V6-1215S3	9-18	22	312	15	0	200	80	47
V6-1224S3	9-18	22	313	24	0	125	80	22
V6-123R3D3	9-18	22	343	±3.3	0	±450	72	±220
V6-1205D3	9-18	22	328	±5	0	±300	76	±220
V6-1209D3	9-18	22	312	±9	0	±167	80	±33
V6-1212D3	9-18	22	312	±12	0	±125	80	±22
V6-1215D3	9-18	22	312	±15	0	±100	80	±22
V6-1224D3	9-18	22	313	±24	0	±63	80	±10
V6-243R3S3	18-36	12	171	3.3	0	900	72	470
V6-2405S3	18-36	12	164	5	0	600	76	470
V6-2409S3	18-36	12	160	9	0	333	78	68
V6-2412S3	18-36	12	156	12	0	250	80	47
V6-2415S3	18-36	12	152	15	0	200	82	47
V6-2424S3	18-36	12	153	24	0	125	82	22
V6-243R3D3	18-36	12	171	±3.3	0	±450	72	±220
V6-2405D3	18-36	12	160	±5	0	±300	78	±220
V6-2409D3	18-36	12	156	±9	0	±167	80	±33
V6-2412D3	18-36	12	152	±12	0	±125	82	±22
V6-2415D3	18-36	12	152	±15	0	±100	82	±22
V6-2424D3	18-36	12	153	±24	0	±63	82	±10
V6-483R3S3	36-72	8	86	3.3	0	900	72	470
V6-4805S3	36-72	8	82	5	0	600	76	470
V6-4809S3	36-72	8	80	9	0	333	78	68
V6-4812S3	36-72	8	78	12	0	250	80	47
V6-4815S3	36-72	8	78	15	0	200	80	47
V6-4824S3	36-72	8	78	24	0	125	80	22

Suffix "H" means 3.5KVdc isolation

Suffix "P" means Plastic case instead of standard Metal Case

VD - 3W 2:1 Regulated Single & Dual output


MODEL NUMBER	INPUT Voltage Range (Vdc)	INPUT Current		OUTPUT Voltage (Vdc)	OUTPUT Current		EFFICIENCY @FL(%)	Capacitor Load(uF)
		No-Load (mA)	Full Load (mA)		Min. load (mA)	Full load (mA)		
V6-483R3D3	36-72	8	86	±3.3	0	±450	72	±220
V6-4805D3	36-72	8	82	±5	0	±300	76	±220
V6-4809D3	36-72	8	80	±9	0	±167	78	±33
V6-4812D3	36-72	8	78	±12	0	±125	80	±22
V6-4815D3	36-72	8	78	±15	0	±100	80	±22
V6-4824D3	36-72	8	78	±24	0	±63	80	±10

Suffix "H" means 3.5KVdc isolation


Suffix "P" means Plastic case instead of standard Metal Case

NOTE


1. Typical value at nominal input voltage and full load.
2. Test by nominal input voltage and constant resistor load.
3. Measured Input reflected ripple current with a simulated source inductance of 12uH.
4. Exceeding the absolute ratings of the unit could cause damage. It is not allowed for continuous operating.



12 Models




24 Models



48 Models


VD - 3W 2:1 Regulated Single & Dual output

MECHANICAL SPECIFICATIONS



PIN CONNECTIONS				
PIN NUMBER	SINGLE	DUAL	SINGLE-H	DUAL-H
1	+V Input	+V Input	N.P.	N.P.
2	N.C.	-V Output	-V Input	-V Input
3	N.C.	Common	-V Input	-V Input
9	N.P.	N.P.	N.P.	Common
10	-V Output	Common	N.P.	N.P.
11	+V Output	+V Output	N.C.	-V Output
12	-V Input	-V Input	N.P.	N.P.
13	-V Input	-V Input	N.P.	N.P.
14	+V Output	+V Output	+V Output	+V Output
15	-V Output	Common	N.P.	N.P.
16	N.P.	N.P.	-V Output	Common
22	N.C.	Common	+V Input	+V Input
23	N.C.	-V Output	+V Input	+V Input
24	+V Input	+V Input	N.P.	N.P.

MECHANICAL SPECIFICATIONS



PIN CONNECTIONS				
PIN NUMBER	SINGLE	DUAL	SINGLE-H	DUAL-H
1	+V Input	+V Input	N.P.	N.P.
2	N.C.	-V Output	-V Input	-V Input
3	N.C.	Common	-V Input	-V Input
9	N.P.	N.P.	N.P.	Common
10	-V Output	Common	N.P.	N.P.
11	+V Output	+V Output	N.C.	-V Output
12	-V Input	-V Input	N.P.	N.P.
13	-V Input	-V Input	N.P.	N.P.
14	+V Output	+V Output	+V Output	+V Output
15	-V Output	Common	N.P.	N.P.
16	N.P.	N.P.	-V Output	Common
22	N.C.	Common	+V Input	+V Input
23	N.C.	-V Output	+V Input	+V Input
24	+V Input	+V Input	N.P.	N.P.