MTi-610

- Small, IP51-rated IMU
- Factory-calibrated inertial data
- Full Graphical User Interface (GUI) and Software Development Kit (SDK) available

The MTi-610 is a Inertial Measurement Unit with a small form-factor design for deep integration into your application. Building on the proven Xsens MTi 600-series technology it enables a robust and easy to use motion tracking. It is designed for easy integration and seamless interfacing with other equipment.

The MTi-610 is supported by the MT Software Suite which includes MT Manager (GUI for Windows/Linux), SDK, example codes and drivers for many platforms including ROS.



- White label and OEM integration options available
- 3D models available on request

IMU	performance
-----	-------------

Accelerometer		Calibrated
Gyroscope		Calibrated
Strapdown Integra	ation (SDI)	 Yes

Gyroscope

Standard full range ————	2000 deg/s
In-run bias stability	8 deg/h
Bandwidth (-3dB)	520 Hz
Noise Density	0.007 °/s/√Hz
g-sensitivity (calibr.)	0.1 º/s/g

Accelerometer

Standard full range	10 g
In-run bias stability	10 (x,y) 15(z) μg
Bandwidth (-3dB)	500 Hz
Noise Density	60 μg/√Hz

Magnetometer

Standard full range ———	+/- 8 G
Total RMS noise	1 mG
Non-linearity	0.2%
Resolution ————	0.25 mG

Barometer

Standard full range ————	300-1250 hPa
Total RMS noise	1.2 Pa
Relative accuracy	+/- 8 Pa (~0.5m)

This document is informational and not binding.

Complete and detailed specifications are available at
mtidocs.movella.com

Mechanical

IP-rating ————	IP51
Operating Temperature ———	-40 to 85 °C
Casing material	PC-ABS
Mounting orientation ————	No restriction, full 360° in all axes
Dimensions —————	28x31.5x13 mm
Connector	Main: Phoenix Contact 16 pin, 1.27 mm
	pitch
Weight —	8.9 g
Certifications	CE, FCC, RoHS

Electrical

Input voltage	4.5	to 24V
Power consumption (typ)	<0.	5 W

Interfaces / IO

Interfaces —————	UART, CAN, RS232
Sync Options	SyncIn, SyncOut, ClockSync
Protocols ——————	Xbus, ASCII (NMEA) or CAN
Clock drift	10 ppm (or external)
Output Frequency	Up to 2kHz, 400Hz SDI
Built-in-self test	Gyr, Acc, Mag, Baro

Software Suite

Software Suite	
GUI (Windows/Linux)	MT Manager, Firmware updater,
	Magnetic Field Mapper
SDK (Example code)	C++, C#, Python, Matlab, Nucleo,
	public source code
Drivers ————	LabVIEW, ROS, GO
Support —————	Online manuals, community and
	knowledge base



