

BAC3S05DC

Note: If you have not downloaded this document from our official website, please note that the information provided may not be the most current. Please download the latest datasheet of BAC3S05DC from the official website of Murata

http://www.murata.com/en-gb/products/productdetail?partno=BAC3S05DC



Applications

| Unsuitable | Please be sure to read and comply with | |
|--------------|--|--|
| Applications | these "Precautions for use." | |
| | Consumer equipment,Industrial | |
| | Equipment | |
| | Please refer to Our Website and | |
| | specifications, etc. for information about | |
| Specific | the performance, functions, quality, | |
| Applications | management, and safety required for | |
| | the above applications, and use | |
| | Products after confirming the | |
| | performance and reliability of the actual | |
| | Product. | |
| Recommended | Isolated AC-DC power supply | |
| Applications | | |

Appearance & Shape





5V 0.6A, Isolated 3W Regulated Single Output 4kVAC, AC-DC Converters, 85-264VAC/70-370VDC Input

1 of 2

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.







BAC3S05DC

Note: If you have not downloaded this document from our official website, please note that the information provided may not be the most current. Please download the latest datasheet of BAC3S05DC from the official website of Murata

http://www.murata.com/en-gb/products/productdetail?partno=BAC3S05DC

Specifications

| Output power (W)Max | 3W |
|----------------------------|------------------|
| Vin (VAC) | 85Vac to 264Vac |
| Vin (VAC)typ | 230Vac |
| Vin (VDC) | 120Vdc to 370Vdc |
| Vout(V) | 5V |
| Vout(V)typ | 5V |
| LineRegulation (%) | -0.5% to 0.5% |
| LoadRegulation (%) | -1% to 1% |
| Isolation Voltage (V) | 4700V |
| Efficiency (%) | 77% |
| Size(mm)W | 25.4mm |
| Size(mm)L | 25.4mm |
| Size(mm)T | 16.3mm |
| Operatingtemperature(degC) | -40°C to 85°C |
| Outputs (#) | 1 |
| lout(A)Max | 0.6A |
| Package | DIP |
| Productseries | BAC3 |

| | The BAC3 series delivers an |
|-------------------------|------------------------------|
| | output power of 3 |
| | watts from -40°C to 65°C, |
| | operating up to 85°C |
| | with derating, from AC or DC |
| | input voltages. |
| | The BAC3 series small |
| | footprint is EMC class |
| | B compliant without the need |
| | of any external |
| | components. The BAC3 series |
| Product Series Features | is suited to medical |
| | applications with 1 MOPP and |
| | 2 MOOP. |
| | With high efficiency at low |
| | loads and low no load |
| | power consumption, the BAC3 |
| | supports standby |
| | mode operation for |
| | applications in industrial, |
| | medical, automation, IOT as |
| | well as household |
| | and home automation. |
| | UL62368-1, EN62368-1, |
| Safety Approval | IEC61558-1, IEC61558-2-16, |
| | ANSI/AAMI ES60601-1 |
| Brand | Murata Power Solutions |
| | |

2 of 2

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

