

Note: If you have not downloaded this document from our official website, please note that the information provided may not be the most current. Please download the latest datasheet of BAC3S24DC from the official website of Murata

## BAC3S24DC



Recommended

New





### **Applications**

Unsuitable	Please be sure to read and comply with	
Applications	these "Precautions for use."	
Specific Applications	Consumer equipment,Industrial	
	Equipment	
	Please refer to Our Website and	
	specifications, etc. for information about	
	the performance, functions, quality,	
	management, and safety required for	
	the above applications, and use	
	Products after confirming the	
	performance and reliability of the actual	
	Product.	
Recommended	Indiated AC DC navyor cumply	
Applications	Isolated AC-DC power supply	



### **Features**

24V 0.125A, Isolated 3W Regulated Single Output 4kVAC, AC-DC Converters, 85-264VAC/70-370VDC Input



## Appearance & Shape



1 of 2

- 1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
- 2. This datasheet has only typical specifications because there is no space for detailed specifications.
- Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





### Product Search Data Sheet

information provided may not be the most current. Please download the latest datasheet of BAC3S24DC from the official website of Murata

Note: If you have not downloaded this document from our official website, please note that the

# BAC3S24DC



## **Specifications**

Output power (W)Max	3W
Vin (VAC)	85Vac to 264Vac
Vin (VAC)typ	230Vac
Vin (VDC)	120Vdc to 370Vdc
Vout(V)	24V
Vout(V)typ	24V
LineRegulation (%)	-0.5% to 0.5%
LoadRegulation (%)	-1% to 1%
Isolation Voltage (V)	4700V
Efficiency (%)	81%
Size(mm)W	25.4mm
Size(mm)L	25.4mm
Size(mm)T	16.3mm
Operatingtemperature(degC)	-40°C to 85°C
Outputs (#)	1
lout(A)Max	0.125A
Package	DIP
Productseries	BAC3

	T. DAGG : 1.1
	The BAC3 series delivers an
	output power of 3
	watts from -40°C to 65°C,
	operating up to 85°C
	with derating, from AC or DC
	input voltages.
	The BAC3 series small
	footprint is EMC class
	B compliant without the need
	of any external
	components. The BAC3 series
Product Series Features	is suited to medical
	applications with 1 MOPP and
	2 MOOP.
	With high efficiency at low
	loads and low no load
	power consumption, the BAC3
	supports standby
	mode operation for
	applications in industrial,
	medical, automation, IOT as
	well as household
	and home automation.
	UL62368-1, EN62368-1,
Safety Approval	IEC61558-1, IEC61558-2-16,
	ANSI/AAMI ES60601-1
Brand	Murata Power Solutions

2 of 2

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

