

Product Search Data Sheet

Note: This datasheet may be out of date. Please download the latest datasheet of FTN18WF104F01RT from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=FTN18WF104F01RT

FTN18WF104F01RT












Appearance & Shape







Features

- 1. This product is built in our chip NTC thermistor.
- 2. Excellent environmental resistance and mechanical strength by resin package.
- 3. Surface of the resin package is flat and insulative, it is possible to mount to a metallic steel case directly.
- 4. Quick response
- 5. Product change over time is little and stable.
- 6. Reflow and wire bonding available
- 8. UL/cULcertified product. (UL1434, File No. E137188)



Applications

Limited Usage	Consumer Grade
---------------	----------------



Packaging Information

Packaging	Specifications	Standard Packing Quantity
RT	180mm Paper Tape	4000

1 of 3

- 1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
- 2. This datasheet has only typical specifications because there is no space for detailed specifications
- Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





Product Search Data Sheet

Note: This datasheet may be out of date. Please download the latest datasheet of FTN18WF104F01RT from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=FTN18WF104F01RT

FTN18WF104F01RT



Specifications

Resistance (25°C)	100kΩ	
Resistance Value Tolerance	±1%	
(at 25°C)		
B-Constant (25/50°C)	4250K	
B-Constant (25/50°C)	±1%	
Tolerance	1170	
B-Constant(25/80°C)	4303K	
(Reference Value)	40001	
B-Constant(25/85°C)	4311K	
(Reference Value)		
B-Constant(25/100°C)	4334K	
(Reference Value)		
Max. Voltage	5V	
Maximum Operating Current	0.031mA	
(25°C)	0.03 HHA	
Rated Electric Power (25°C)	4.5mW	
Typical Dissipation Constant	1mW/°C	
(25°C)	111177 C	
Operating Temperature	-40°C to 125°C	
Range		
Thermal Time Constant	2s	
Lead Shape	Insulation type	
Shape	SMD	
Mass	0.0014g	
MSL	3	

2 of 3

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





FTN18WF104F01RT


Note: This datasheet may be out of date.

Please download the latest datasheet of FTN18WF104F01RT from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=FTN18WF104F01RT



Product Data



Resistance-Temperature Characteristics

3 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

