



MVAC250-24AFT

OPEN FRAME AC-DC 250 Watt, 24V Main Output, 12V FAN OUTPUT 5V STANDBY Front-End Power Supply with TERMINAL BLOCK

Recommended

In Production

?



[DATASHEET \(PDF\)](#)

[ADD TO COMPARE LIST](#)

[CONTACT US](#)

[SAMPLE REQUEST](#)

[TECHNICAL SUPPORT](#)

[REQUEST A QUOTE](#)

[STOCKCHECK: WHERE TO BUY](#)

[3D MODELS](#)

[AC-DC APPLICATION NOTES](#)

Technical Information

Total Output Power (W)	250
Input Voltage Range (V)	90 to 264
Output Voltage 1 (V)	24
Output Voltage 2 (V)	12
Output Voltage 3 (V)	5
Efficiency (%)	94
Operating Temp. Range (C)	-10 to 70
Design Origin	Murata Power Solutions
Dimensions (inch)	3 x 5 x 1.4
Quality	Safety – Medical Standards 2 x MOPP (Primary-Secondary) IEC60601-1 (Ed. 3) – CB Cert and Report ANSI/AAMI ES60601-1 (2005+C1:09+A2:10) CAN/CSA 22.2 No. 60601-1 (2008) 3rd Edition EN60601-1:2006+CORR:2010
Series Headline	MVAC250 Series
Series Description	The MVAC250 series switching power supplies utilize advanced component and circuit technologies to deliver high efficiency. Designed for medical, computing, communications, telecom and other OEM applications to satisfy 1U height design considerations, the MVAC400 Series measures only 3.0" x 5.0" x 1.40". All models offer universal AC input with active power factor correction (PFC) and compliance to worldwide safety and EMC standards.

Any known Murata Power Solutions replacement product for the discontinued Murata Power Solutions type number is reference only information. Murata Power Solutions replacement part designation is NOT intended a statement of warranty, or an indication that the listed replacement product meets the same form, fit, function or performance of the discontinued product until such time as Murata Power Solutions customers or distributors qualify such product to their specifications. Therefore, please ensure to check datasheet, order the samples and/ or to contact for our technical support members in your area for further support