Note: This datasheet may be out of date.

Please download the latest datasheet of NCP03WF683F05RL from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=NCP03WF683F05RL

# NCP03WF683F05RL












### Appearance & Shape







### Packaging Information

Packaging		Standard Packing Quantity
RL	180mm Paper Tape	15000



### **Features**

- 1. Excellent solderability and high stability in environment
- 2. Excellent long time aging stability
- 3. High accuracy in resistance and B-Constant
- 4. Reflow soldering possible
- 5. Lead is not contained in the product.
- 6. NCP series are recognized by UL/cUL (UL1434, File No.E137188).



### **Applications**

Limited Usage	Mobile Application, Tablet PC, Wearable	
	Temperature compensation for	
	transistor, IC and   crystal	
Other Usage	oscillator in mobile communications 2.	
	Temperature sensor for rechargeable	
	batteries	

1 of 3

#### Attention

- 1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
- 2. This datasheet has only typical specifications because there is no space for detailed specifications.
- Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





# NCP03WF683F05RL

Note: This datasheet may be out of date.

Please download the latest datasheet of NCP03WF683F05RL from the official website of Murata

Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=NCP03WF683F05RL



## **Specifications**

Resistance (25°C)	68kΩ	
Resistance Value Tolerance	+1%	
(at 25°C)	1170	
B-Constant (25/50°C)	4250K	
B-Constant (25/50°C)	±1%	
Tolerance		
B-Constant(25/80°C)	4303K	
(Reference Value)		
B-Constant(25/85°C)	4311K	
(Reference Value)	401110	
B-Constant(25/100°C)	4334K	
(Reference Value)		
Max. Voltage	5V	
Maximum Operating Current	0.038mA	
(25°C)		
Typical Dissipation Constant	1mW/°C	
(25°C)		
Operating Temperature	-40°C to 125°C	
Range	70 0 10 120 0	
Size Code (in mm)	0.6x0.3mm	
Size Code (in inch)	0.2x0.1inch	
Shape	SMD	
Mass	0.00026g	

2 of 3

#### Attention

1.This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.




Manufacturing Co., Ltd.


#### http://www.murata.com/en-us/products/productdetail?partno=NCP03WF683F05RL

Note: This datasheet may be out of date.

# NCP03WF683F05RL







Please download the latest datasheet of NCP03WF683F05RL from the official website of Murata

Resistance-Temperature Characteristics

Maximum Operating Voltage Reduction Characteristics

3 of 3

#### Attentior

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

