

Product Search Data Sheet

NCU15WM224E60RC


In Production	Recommended	New	RoHS	REACH

## Applications

Unsuitable	Please be sure to read and comply with		
Applications	these "Precautions for use."		
	Consumer equipment, Industrial		
	Equipment,Medical equipment [GHTF		
	A/B]		
	Please refer to Our Website and specifications, etc. for information about		
Specific			
Applications	the performance, functions, quality,		
Applications	management, and safety required for		
	the above applications, and use		
	Products after confirming the		
	performance and reliability of the actual		
	Product.		

# Appearance & Shape






Note: If you have not downloaded this document from our official website, please note that the information provided may not be the most current.

Please download the latest datasheet of NCU15WM224E60RC from the official website of Murata

http://www.murata.com/en/products/productdetail?partno=NCU15WM224E60RC

# Packaging Information

Packaging	Specifications	Standard Packing Quantity
RC	180mm Paper Tape	10000



- 1. Excellent solderability and high stability in environment
- 2. Excellent long time aging stability
- 3. High accuracy in resistance and B-Constant
- 4. Reflow soldering possible

5. Same B-constant in the same resistance in the three sizes (0603 size / 0402 size)

- Easy to use smaller size in the circuits
- 6. Lead is not contained in the product.



## Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





# NCU15WM224E60RC

Note: If you have not downloaded this document from our official website, please note that the information provided may not be the most current.

Please download the latest datasheet of NCU15WM224E60RC from the official website of Murata

http://www.murata.com/en/products/productdetail?partno=NCU15WM224E60RC



#### Resistance (25°C) 220kΩ Resistance Value Tolerance ±3% (at 25°C) B-Constant (25/50°C) 4500K B-Constant (25/50°C) ±3% Tolerance B-Constant(25/80°C) 4571K (Reference Value) B-Constant(25/85°C) 4582K (Reference Value) B-Constant(25/100°C) 4614K (Reference Value) 5V Max. Voltage Maximum Operating Current 0.021mA (25°C) Typical Dissipation Constant 1mW/°C (25°C) **Operating Temperature** -55°C to 125°C Range Size Code (in mm) 1.0x0.5mm 0.4x0.2inch Size Code (in inch) SMD Shape 0.0012g Mass MSL 1

> Glossary of NTC thermistors

Related documents (UL, RoHS, etc.)

## 2 of 3

### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.




# NCU15WM224E60RC

Note: If you have not downloaded this document from our official website, please note that the information provided may not be the most current.


Please download the latest datasheet of NCU15WM224E60RC from the official website of Murata

http://www.murata.com/en/products/productdetail?partno=NCU15WM224E60RC






**Resistance-Temperature Characteristics** 



Max. Voltage, Max. Operating Voltage/Current Reduction Curve



**Temperature Error Characteristics** 

3 of 3

## Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering

