


HPR1XX

0.75 Watt Single Output DC/DC Converter



- Low Cost
- Multiple Package Styles
- Internal Input and Output
- Filtering
- Non-Conductive Case
- High Output Power Density: 10 Watts/Inch³
- Extended Temperature Range: -25°C to +85°C
- Efficiency to 79%

ISO9001
CERTIFIED

The HPR1XX Series uses advanced circuit design and packaging technology to deliver superior reliability and performance. A 170kHz push-pull oscillator is used in the input stage. Beat-frequency oscillation problems are reduced when using the HPR1XX Series with high frequency isolation amplifiers.

Reduced parts count and high efficiency add to the reliability of the

HPR1XX Series. The high efficiency of the HPR1XX Series means less internal power dissipation, as low as 190mW. With reduced heat dissipation the HPR1XX Series can operate at higher temperatures with no degradation. In addition, the high efficiency of the HPR1XX Series means the series is able to offer greater than 10 W/inch³ of output power density. Operation down to

no load will not impact the reliability of the series, although a ≥ 1 mA minimum load is needed to realize published specifications.

The HPR1XX Series provides the user a low cost converter without sacrificing reliability. The use of surface mounted devices and advanced manufacturing technologies make it possible to offer premium performance and low cost.

SPECIFICATIONS All specifications are typical at $T_A = +25^\circ\text{C}$ nominal input voltage unless otherwise specified.

PRODUCT SELECTION CHART

MODEL	NOMINAL INPUT VOLTAGE (VDC)	RATED OUTPUT VOLTAGE (VDC)	RATED OUTPUT CURRENT (mA)	INPUT CURRENT		REFLECTED RIPPLE CURRENT (mAp-p)	EFFICIENCY (%)
				NO LOAD (mA)	RATED LOAD (mA)		
HPR100	5	5	150	20	216	10	69
HPR101	5	12	62	20	212	5	70
HPR102	5	15	50	20	212	5	71
HPR103	5	± 5	± 75	20	218	5	68
HPR104	5	± 12	± 30	20	212	5	68
HPR105	5	± 15	± 25	20	200	5	75
HPR106	12	5	150	10	90	5	69
HPR107	12	12	62	10	81	5	77
HPR108	12	15	50	10	81	5	77
HPR109	12	± 5	± 75	10	88	5	71
HPR110	12	± 12	± 30	10	81	5	74
HPR111	12	± 15	± 25	10	81	5	77
HPR112	15	5	150	8	72	5	69
HPR113	15	12	62	8	72	5	69
HPR114	15	15	50	8	72	5	69
HPR115	15	± 5	± 75	8	72	5	69
HPR116	15	± 12	± 30	8	63	5	76
HPR117	15	± 15	± 25	8	63	5	79
HPR118	24	5	150	8	48	15	65
HPR119	24	12	62	8	48	15	65
HPR120	24	15	50	8	45	15	76
HPR121	24	± 5	± 75	8	45	15	69
HPR122	24	± 12	± 30	8	45	15	67
HPR123	24	± 15	± 25	8	45	15	69

Note: Other input to output voltages may be available. Please contact factory.

Product: www.cdpoweronline.com


HPR1XX REV M 1/04

SPECIFICATIONS, ALL MODELS


Specifications are at $T_A = +25^\circ\text{C}$ nominal input voltage unless otherwise specified.

	PARAMETER	CONDITIONS	MIN	TYP	MAX	UNITS
OUTPUT	INPUT					
	Voltage Range		4.5	5	5.5	VDC
			10.8	12	13.2	VDC
			13.5	15	16.5	VDC
			21.6	24	26.4	VDC
	Voltage Rise Time	See Typical Performance Curves & Application Notes: "Capacitive Loading Effects on Start-Up of DC/DC Converters"				
	OUTPUT					
	Rated Power			750		mW
	Voltage Setpoint Accuracy	Rated Load, Nominal V_{IN}			± 5	%
	Ripple & Noise	BW = DC to 10MHz		150		mVp-p
GENERAL		BW = 10Hz to 2MHz		30		mVrms
	Voltage (Over Input Voltage Range)	1mA Load, $V_{OUT} = 5\text{V}$			7	VDC
		1mA Load, $V_{OUT} = 12\text{V}$			15	VDC
		1mA Load, $V_{OUT} = 15\text{V}$			18	VDC
	Temperature Coefficient			.01		%/ $^\circ\text{C}$
	REGULATION					
	Line Regulation	High Line to Low Line		1		%/ $\%V_{IN}$
	GENERAL ISOLATION					
	Rated Voltage		750			VDC
	Test Voltage	60 Hz, 10 Seconds	750			Vrms (1060pk)
	Resistance			10		GW
	Capacitance			25	100	pF
	Leakage Current	$V_{ISO} = 240\text{VAC}$, 60Hz		2	8.5	mArms
	Switching Frequency			170		kHz
	Frequency Change	Over Line and Load		24		%
	Package Weight			2		g
	MTTF per MIL-HDBK-217, Rev. F*	Circuit Stress Method				
	Ground Benign	$T_A = +25^\circ\text{C}$		7.9		MHr
	Fixed Ground	$T_A = +35^\circ\text{C}$		1.9		MHr
	Naval Sheltered	$T_A = +35^\circ\text{C}$		1.2		MHr
	Airborne Uninhabited Fighter	$T_A = +35^\circ\text{C}$		300		kHr
	TEMPERATURE					
	Specification		-25	+25	+85	$^\circ\text{C}$
	Operation		-40		+100	$^\circ\text{C}$
	Storage		-40		+110	$^\circ\text{C}$

RECOMMENDED LAND PATTERN











RECOMMENDED REFLOW PROFILE**






** This profile is only applicable to the surface mount package devices.

TYPICAL PERFORMANCE CURVES

Specifications are at $T_A = +25^\circ\text{C}$ nominal input voltage, nominal load, recommended external components applied, unless otherwise specified. (Refer to Application Note DCAN-9 at www.cdpoweronline.com)



SAFE OPERATING AREA




NOTES:

- When operated within the SAFE OPERATING AREA as defined by the above curves, the output voltage of HPR1XX devices is guaranteed to be within 95% of its steady-state value within 100 milliseconds after the input voltage has reached 95% of its steady-state value.
- For dual output models, total load capacitance is the sum of the capacitances on the plus and minus outputs.

MECHANICAL

"SIP" PACKAGE/PINOUT



Notes:

All dimensions are in inches (millimeters).

GRID: 0.100 inches (2.54 millimeters)

PIN PLACEMENT TOLERANCE: ± 0.015


*Common pin not present on single output models.

PIN CONNECTIONS

1. +VIN
2. -VIN
4. -VOUT
5. COM*
6. +VOUT

PACKAGE/PINOUT "V" AND "W"


DIP PACKAGE



PIN CONNECTIONS

PIN#	SINGLES	DUALS	PIN#	SINGLES	DUALS
1	+VIN	+VIN	7	+VOUT	+VOUT
2	-VIN	-VIN	8	NC	NC
3	NC	NC	9	NC	NC
4	NC	NC	10	NC	NC
5	-VOUT	-VOUT	11	NC	NC
6	NC	Common	13	NC	NC
			14	NC	NC

SMD PACKAGE



NOTES:

NC = Do Not Connect.

Duplicate pin functions are internally connected.

All dimensions are in inches (millimeters).

GRID: 0.100 inches (2.54 millimeters)

ABSOLUTE MAXIMUM RATINGS

Internal Power Dissipation..... 450mW
 ShortCircuitDuration..... Momentary
 Lead Temperature (soldering, 10 seconds max) .. +300°C *

* NOTE: Refer to Reflow Profile for SMD Models.

ORDERING INFORMATION

Device Family **HPR** **1XX** **V/W**
 HPR Indicates DC/DC Converter
 Model Number _____
 Selected from Table of Electrical Characteristics
 Package Option _____
 There is "no" package designator for the SIP package
 V = DIP Package

Power Electronics Division, Americas
 3400 E Britannia Drive, Tucson, Arizona 85706
 Tel: 800.547.2537 Fax: 520.295.4197

C&D Technologies, EMEA/AP
 Milton Keynes MK14 5BU UK
 Tel: +44 (0)1908 615232 Fax: +44 (0)1908 617545

Any data, prices, descriptions or specifications presented herein are subject to revision by C&D Technologies, Inc. without notice. While such information is believed to be accurate as indicated herein, C&D Technologies, Inc. makes no warranty and hereby disclaims all warranties, express or implied, with regard to the accuracy or completeness of such information. Further, because the product(s) featured herein may be used under conditions beyond its control, C&D Technologies, Inc. hereby disclaims all warranties, either express or implied, concerning the fitness or suitability of such product(s) for any particular use or in any specific application or arising from any course of dealing or usage of trade. The user is solely responsible for determining the suitability of the product(s) featured herein for user's intended purpose and in user's specific application. C&D Technologies, Inc. does not warrant or recommend that any of its products be used in any life support or aviation or aerospace applications.