


maxpower 180 W, single

SCHROFF



Other Views



Catalog Number: 13100-153

[Back To Product](#)

- Wide input voltage range 90 ... 254 VAC and 100 ... 360 VDC with active Power Factor Correction (PFC)
- Single output voltage
- Integrated active decoupling for redundancy operation
- Active Current Share Bus (CSB)
- Signalling: Output voltage OK
- Efficiency up to 87 %

Application:

19" compatible

Specification:

Universal 19"

Output voltages:

1

Note:

Please order front panel separatelyOutput data for mains voltage > 190 VAC, TA = 0 ... 50 °CCustomised front panels available via www.frontpanelexpress.eu

Type:

Switched-mode PSU

Power type:

AC/DC

Output power:

100 ... 180 W



Select product specifications before modifying or adding to project list or requesting a quote.

Current-defining

Voltage-defining

[Clear Selection](#)

Quantity

Modify Product ▶

Add Item to Project List +

Documents

- Main Catalog - Power supply systems (ROW)
- User manual
- Declaration of conformity
- Declaration of conformity
- Safety instructions
- How is the current share bus (CSB) connected?

Links

- Configurator - Power Supplies Units
- Native CAD files

Technical Data



Voltage1 V	24.0	Connector pin-out	Connection
Current1 A	7.0	-----	-----
Power W	168.0	Pin 4	Output + V1
Description	MAX 180-124	Pin 6	Output + V1
Height U	3	Pin 8	Sense + V1
Width HP	8	Pin 10	Sense V0 V1
		Pin 12	Output 0V V1
		Pin 14	Output 0V V1
		Pin 16	Output + V1
		Pin 18	Output 0V V1

Pin 20	Test
Pin 22	CSB
Pin 24	DC output OK
Pin 26	-
Pin 28	L
Pin 30	N
Pin 32	PE

Delivery Comprises:

Item	Quantity	Description
1	1	19" compatible power supply, height 3 U, width A: 8 HP, depth 171.93 mm (160 mm board depth), connector H 15 M, coding strip (fitted)

Accessories

	Stainless steel EMC gasket, 3 U, 97 mm, stainless steel, two pieces necessary per front panel, PU 10 pcs	21101-705	Add Item to Project List +
	Coding, PU (1 keying/coding strip, 2 pieces keying/coding pins)	60800-123	Add Item to Project List +
	Front panel, 8 HP, Al extrusion, front anodised, rear iridescent green chromated, shielded with fixed textile gasket, incl. assembly kit, 1 piece	31006-677	Add Item to Project List +
	Connector H 15 F, FASTON connection, 1 piece	69001-733	Add Item to Project List +

EXPLORE	CONTACT	DOWNLOAD
About Us	Customer Service	Download Center
Services & Capabilities	Find a Sales Office or Distributor	Reference Projects
News & Events	Global Locations	Videos
Newsletter Subscriptions	Product Compliance & Certifications	Product Configurators
Strategic Partnerships	Partner Login	Warranties and Terms of Sale & Procurement
Investor Relations		

