

OV12A10-OV12A1B 12MP product brief



12-Megapixel PureCel®Plus Sensors for Dual and Single Cameras in Mobile Applications



available in
a lead-free
package

OmniVision's color OV12A10 and monochrome OV12A1B are 12-megapixel image sensors designed to deliver premium image quality for both single-camera solutions and, in particular, dual-camera solutions in high-end and mainstream mobile markets. These 1.25-micron image sensors enable mobile dual-camera solutions to produce advanced DSLR features such as optical zoom, high dynamic range (HDR), and hand jitter reduction with excellent low-light performance and low power consumption.

The OV12A10 and OV12A1B sensors are built on OmniVision's PureCel®Plus technology, which implements buried color filter array (BCFA) and deep

trench isolation (DTI) for dramatically reduced color crosstalk, as well as improved signal-to-noise ratio (SNR) and sensor angular response.

The 1/2.8-inch OV12A10 and OV12A1B include phase detection autofocus (PDAF) support and capture full-resolution 12-megapixel resolution at 30 frames per second (fps), 4K2K video at 30 fps, and 1080p resolution at 90 fps.

Find out more at www.ovt.com.




Applications

- Smartphones and Feature Phones
- Tablets
- PC Multimedia
- Wearables

Product Features

- 1.25 μm x 1.25 μm pixel
- optical size of 1/2.8"
- 34.5° CRA
- 12MP at 30 fps
- programmable controls for:
 - frame rate
 - mirror and flip
 - cropping
 - windowing
- supports images sizes:
 - 12MP (4096x3072)
 - 4K2K (3840x2160)
 - 1080p (1920x1080), and more
- 416 bytes of embedded one-time programmable (OTP) memory for customer use
- support for output formats:
 - 10-bit RGB RAW
- two-wire serial bus control (SCCB)
- MIPI serial output interface (1-lane, 2-lane, or 4-lane)
- two on-chip phase lock loops (PLLs)
- 2x binning support
- image quality controls:
 - defect pixel correction
 - automatic black level calibration
 - lens shading correction
- built-in temperature sensor
- suitable for module size of 8.5 x 8.5 x 4.5 mm

OV12A10-OV12A1B




Ordering Information

- OV12A10-GA5A**
(color, chip probing, 150 μm backgrounding, reconstructed wafer)
- OV12A1B-GA5A-Z**
(b&w, chip probing, 150 μm backgrounding, reconstructed wafer)

Technical Specifications

- active array size:** 4096 x 3072
- maximum image transfer rate:**
 - 12MP (4096x3072): 30 fps
 - 4K2K: 30 fps
 - 1080p: 90 fps
 - 720p: 120 fps
- power supply:**
 - analog: 2.7 to 3.0V (2.8V nominal)
 - core: 1.14 to 1.26V (1.2V nominal)
 - I/O: 1.7 to 1.9V (1.8V nominal)
- power requirements:**
 - active: 217 mW (typical for 12MP @ 30 fps)
 - standby: 890 μW (typical)
 - XSHUTDOWN: 1.5 μW (typical)
- temperature range:**
 - operating: -30°C to +85°C junction temperature
 - stable image: 0°C to +60°C junction temperature
- output interface:** 4-lane MIPI serial output
- output formats:** 10-bit RGB RAW
- lens size:** 1/2.8"
- lens chief ray angle:** 34.5° non-linear
- pixel size:** 1.25 μm x 1.25 μm
- image area:** 5107.10 μm x 3835.30 μm

Functional Block Diagram



4275 Burton Drive
Santa Clara, CA 95054
USA

Tel: +1 408 567 3000
Fax: +1 408 567 3001
www.ovt.com

OmniVision reserves the right to make changes to their products or to discontinue any product or service without further notice. OmniVision, the OmniVision logo and PureCel are registered trademarks of OmniVision Technologies, Inc. All other trademarks are the property of their respective owners.



OmniVision