

A Wide Variety of Electrodes for Long Lasting Reliability

- Standard Electrodes are made of stainless steel (SUS 304) and can be used in applications for purified water.
- SUS316 Electrodes can be used in applications where resistance to corrosion is required. Titanium and HAS Electrodes can be used in applications where resistance to acid is required.
- For applications where long electrodes are required, a connection nut and two Lock Nuts can be used to extend the electrodes 1 m at a time.



Refer to **Safety Precautions for Electrodes and Electrode Holders**.

Ordering Information

Material indications are provided on all OMRON electrodes, connection nuts, and Lock Nuts.

Electrodes

Select an electrode appropriate for the type of liquid. Refer to *Technical Guide for Level Controllers*.

| Model | Material | Weight (g) | Material indication lines | |
|---------------------------|-------------------|-------------|---------------------------|-----------------------|
| F03-01 SUS304 ELECTRODE | SUS304 | Approx. 170 | 1 line | <div>Electrodes</div> |
| F03-01 SUS316 ELECTRODE | SUS316 | | 2 lines | |
| F03-01 HAS B ELECTRODE | N10665 (See note) | Approx. 195 | 3 lines | |
| F03-01 HAS C ELECTRODE | N10276 (See note) | Approx. 190 | 4 lines | |
| F03-01 TITANIUM ELECTRODE | Titanium | Approx. 100 | 5 lines | |

Note: UNS No. (Unified Numbering System No.) is an international metal designation system that specifies a unique number for each material.

Insulated Electrodes

Electrodes are insulated with a plastic sheath to prevent them from touching each other and to isolate them from debris in the liquid. Before application, strip back about 10 cm of the sheath at the end to ensure sufficient conductivity.

| Model | Sheath |
|---------------------------|--------------------|
| F03-01 SUS304 | Vinyl Tubing |
| F03-01 SUS304 FLUORORESIN | Fluororesin Tubing |
| F03-01 SUS316 | Vinyl Tubing |
| F03-01 SUS316 FLUORORESIN | Fluororesin Tubing |

Note: Tubing comes in 1-m lengths with a sheath thickness of 0.5 mm.

Connecting Nuts

| Model | Material | Weight (g) | Material indication |
|-----------------------------|-------------------------------|------------|---------------------|
| F03-02 SUS304 (See note 1.) | SUS303 (Equivalent to SUS304) | Approx. 12 | Blank |
| F03-02 SUS316 (See note 1.) | SUS316 | | 6 |
| F03-02 HAS B | N10665 (See note 2.) | Approx. 20 | B |
| F03-02 HAS C | N10276 (See note 2.) | | C |
| F03-02 TITANIUM | Titanium | Approx. 6 | T |

- Note:**
1. Spring washers made of the same material are included with the F03-02 SUS304 and F03-02 SUS316. Spring washers are not included with the other models. OMRON does not sell spring washers by themselves.
 2. UNS No. (Unified Numbering System No.) is an international metal designation system that specifies a unique number for each material.

Electrode Sets

An Electrode Set consists of an electrode, a connecting nut, and two Lock Nuts.

| Set model | Components | No. of parts in an set | Weight (g) |
|---------------|-------------------------|------------------------|-------------|
| F03-60 SUS304 | F03-01 SUS304 ELECTRODE | 1 | Approx. 190 |
| | F03-02 SUS304 | 1 | |
| | F03-03 SUS304 | 2 | |
| F03-60 SUS316 | F03-01 SUS316 ELECTRODE | 1 | Approx. 190 |
| | F03-02 SUS316 | 1 | |
| | F03-03 SUS316 | 2 | |

Note: HAS and titanium Electrodes do not come in sets.




Lock Nuts

| Model | Material | Weight (g) | Material indication |
|-----------------------------|-------------------------------|------------|---------------------|
| F03-03 SUS304 (See note 1.) | SUS303 (Equivalent to SUS304) | Approx. 2 | Blank |
| F03-03 SUS316 (See note 1.) | SUS316 | | 6 |
| F03-03 HAS B | N10665 (See note 2.) | Approx. 5 | B |
| F03-03 HAS C | N10276 (See note 2.) | | C |
| F03-03 TITANIUM | Titanium | Approx. 2 | T |


- Note:** 1. Only SUS304 and SUS316 Lock Nuts come with spring washers made of the same material. HAS B, HAS C and TITANIUM don't come with spring washer.
2. UNS No. (Unified Numbering System No.) is an international metal designation system that specifies a unique number for each material.

Electrode Separators

When long electrodes are required, use Separators at each joint (every 1 m) to prevent the Electrodes from touching each other. Use a 1-pole Separator with BF Electrode Holders. The five-pole model can be used with PS-5S and PS-4S Electrode Holders. Separators cannot be used with PS-31 Electrode Holders.

| Model | No. of Electrodes | Dimensions | Applicable Electrode Holder | Weight (g) | Material | Operating Temperature |
|-----------|-------------------|---|-----------------------------|------------|----------|-----------------------|
| F03-14 1P | 1 |  | BF-□(R) | Approx. 15 | Ceramic | 250°C max. |
| F03-14 3P | 3 |  | PS-3S(R) | Approx. 30 | | |
| F03-14 5P | 5 |  | PS-4S(R) PS-5S(R) | | | |

Note: The Electrode Separators cannot be used unless the Electrodes are coupled.



Note: When using two or more Separators, be careful with the mounting direction of the connecting nut screws which connect electrodes. Avoid the screws from touching each other.

Accessories (Order Separately)


| Application | Model |
|--|--------|
| Protective Cover (for PS-□S and BF-3/-5) | F03-11 |
| Mounting Frame (for PS-□S) | F03-12 |
| Mounting Frame for Installing in Concrete (for PS-□S(R)) | F03-13 |
| Dust-proof Rubber Cap (for PS-31) | F03-31 |

Dimensions of Electrodes and Accessories

Note: All units are in millimeters unless otherwise indicated.


Electrode

F03-01




Lock Nut

**F03-03
SUS304
SUS316
Titanium**




**F03-03
HAS B
HAS C**




Connecting nut


**F03-02
SUS304
SUS316**



**F03-02
HAS B
HAS C**



**F03-02
Titanium**



Note: 1. Dimension when mounting Electrodes.

2. Clamp screws are not provided for HAS B, HAS C, or titanium models. F03-03 Lock Nuts are used to mount Electrodes.

■ Safety Precautions

Refer to *Safety Precautions for All Level Controllers*.

■ Precautions for Correct Use

Cleaning Electrodes

Electrodes are clean when they are dispatched. In the rare occasion that they become dirty during transit or storage, such as forming an oil film on the surface, clean them again before using them.

Operating Environment

Use the Electrode within the ambient operating temperature range of the Holder.

ALL DIMENSIONS SHOWN ARE IN MILLIMETERS.

To convert millimeters into inches, multiply by 0.03937. To convert grams into ounces, multiply by 0.03527.

In the interest of product improvement, specifications are subject to change without notice.

OMRON AUTOMATION AMERICAS HEADQUARTERS • Chicago, IL USA • 847.843.7900 • 800.556.6766 • www.omron247.com

OMRON CANADA, INC. • HEAD OFFICE

Toronto, ON, Canada • 416.286.6465 • 866.986.6766 • www.omron247.com

OMRON ELECTRONICS DE MEXICO • HEAD OFFICE

México DF • 52.55.59.01.43.00 • 01-800-226-6766 • mela@omron.com

OMRON ELECTRONICS DE MEXICO • SALES OFFICE

Apodaca, N.L. • 52.81.11.56.99.20 • 01-800-226-6766 • mela@omron.com

OMRON ELETRÔNICA DO BRASIL LTDA • HEAD OFFICE

São Paulo, SP, Brasil • 55.11.2101.6300 • www.omron.com.br

OMRON ARGENTINA • SALES OFFICE

Cono Sur • 54.11.4783.5300

OMRON CHILE • SALES OFFICE

Santiago • 56.9.9917.3920

OTHER OMRON LATIN AMERICA SALES

54.11.4783.5300

OMRON EUROPE B.V. • Wegalaan 67-69, NL-2132 JD, Hoofddorp, The Netherlands. • +31 (0) 23 568 13 00 • www.industrial.omron.eu

Authorized Distributor:

Controllers & I/O

- Machine Automation Controllers (MAC) • Motion Controllers
- Programmable Logic Controllers (PLC) • Temperature Controllers • Remote I/O

Robotics

- Industrial Robots • Mobile Robots

Operator Interfaces

- Human Machine Interface (HMI)

Motion & Drives

- Machine Automation Controllers (MAC) • Motion Controllers • Servo Systems
- Frequency Inverters

Vision, Measurement & Identification

- Vision Sensors & Systems • Measurement Sensors • Auto Identification Systems

Sensing

- Photoelectric Sensors • Fiber-Optic Sensors • Proximity Sensors
- Rotary Encoders • Ultrasonic Sensors

Safety

- Safety Light Curtains • Safety Laser Scanners • Programmable Safety Systems
- Safety Mats and Edges • Safety Door Switches • Emergency Stop Devices
- Safety Switches & Operator Controls • Safety Monitoring/Force-guided Relays

Control Components

- Power Supplies • Timers • Counters • Programmable Relays
- Digital Panel Meters • Monitoring Products

Switches & Relays

- Limit Switches • Pushbutton Switches • Electromechanical Relays
- Solid State Relays

Software

- Programming & Configuration • Runtime