

Search within category

GO

CMRPSV20SILTLM

The 20A, 120V vertical power strip in black has 20 NEMA 5-20R in-line receptacles. It features one 20A thermal breaker, a red LED surge suppression indicator, a red LED current monitor, and a 10' (3m) power cord with a NEMA L5-20P twist-lock plug. It is UL and c-UL listed and measures 66.3H x 1.9W x 1.6D (1683mm x 47mm x 40mm). It is sold individually.

|                                |                                 |           |                    |              |
|--------------------------------|---------------------------------|-----------|--------------------|--------------|
| Specs                          | Packaging Details               | Documents | ★ Add to Favorites | 🛒 Add to BOM |
| Rack PDU Type                  | Basic Rack PDU with Local Meter |           |                    |              |
| Monitoring                     | Local Meter                     |           |                    |              |
| Remote Outlet Switching        | No                              |           |                    |              |
| Mount Orientation              | Vertical                        |           |                    |              |
| Current Rating (Amps)          | 20A                             |           |                    |              |
| Input Voltage                  | 120V - Single Phase             |           |                    |              |
| Plug Type                      | NEMA L5-20P                     |           |                    |              |
| Output Voltage                 | 120V                            |           |                    |              |
| Receptacle Type                | NEMA 5-20R Duplex               |           |                    |              |
| Total Number of Outlets        | 20                              |           |                    |              |
| Depth (In.)                    | 1.61                            |           |                    |              |
| Depth (mm)                     | 40.9                            |           |                    |              |
| Height (In.)                   | 66.25                           |           |                    |              |
| Height (mm)                    | 1682.8                          |           |                    |              |
| Width (In.)                    | 1.61                            |           |                    |              |
| Width (mm)                     | 40.9                            |           |                    |              |
| Tool-Less Button Spacing (In.) | 64.75                           |           |                    |              |
| Tool-Less Button Spacing (mm)  | 1644.7                          |           |                    |              |
| No. of Rack Spaces             | 0                               |           |                    |              |
| Surge Suppression              | Yes                             |           |                    |              |
| Amps                           | 20A                             |           |                    |              |
| Cable Length                   | 3                               |           |                    |              |
| Length (In.)                   | 68.00                           |           |                    |              |
| UL Recognized                  | Yes                             |           |                    |              |
| Voltage                        | 120V                            |           |                    |              |
| RoHS Compliancy Status         | Compliant                       |           |                    |              |
| Min. Order Qty.                | 1                               |           |                    |              |