

Search within category

GO

GM-A0272BL



SmartZone Gateway-Enabled Rack PDU for aggregate monitoring, vertical 1RU, 20 A, single phase, 208V, 24 IEC C-13 and 6 IEC C-19 receptacles, NEMA L6-20P twist lock plug, LCD display, with Serial port for connection to Gateway. Dimensions: 70"H x 2.50"W x 2.36"D (1778mm x 64mm x 60mm).

Specs	Packaging Details	Documents	★ Add to Favorites	🛒 Add to BOM
UL Listed	No			
Rack PDU Type	Monitored Rack PDU			
Monitoring	Aggregate Current Monitoring			
Remote Outlet Switching	No			
Mount Orientation	Vertical			
Current Rating (Amps)	20A			
Input Voltage	208V - Single Phase			
Plug Type	NEMA L6-20P			
Output Voltage	208V			
Receptacle Type	24 IEC C-13/6 IEC C-19			
Total Number of Outlets	30			
Depth (In.)	2.36			
Depth (mm)	60.0			
Height (In.)	70.00			
Height (mm)	1778.0			
Width (In.)	2.50			
Width (mm)	64.0			
Tool-Less Button Spacing (In.)	64.75			
Tool-Less Button Spacing (mm)	1644.6			
No. of Rack Spaces	0			
Surge Suppression	No			
Amps	20			
Color	Black			
RoHS Compliancy Status	Compliant			
Min. Order Qty.	1			