

Search within category

GO

BUY NOW

DESIGN / INSTALL



**H1M1B1L2N10AXA0**

The 30A, single-phase 208V horizontal basic rack PDU with local meter in black has 10 IEC C-13 receptacles. It features an LCD display, two 20A double-pole magnetic breaker on-off switches, and a 10' (3m) NEMAL6-30P input cord. It measures 1.73H x 17.0W x 8.84D (44mm x 432mm x 225mm). It is sold individually.

Specs

Packaging Details

Documents

★ Add to Favorites

🛒 Add to BOM

Rack PDU Type	Basic with Local Meter Rack PDU
Monitoring	Local Meter
Remote Outlet Switching	No
Mount Orientation	Horizontal
Current Rating (Amps)	30A
Input Voltage	208V - Single Phase
Plug Type	NEMAL6-30P
Output Voltage	208V
Receptacle Type	10 IEC C-13
Total Number of Outlets	10
Depth (In.)	8.84
Depth (mm)	224.5
Height (In.)	1.72
Height (mm)	43.7
Width (In.)	17.00
Width (mm)	431.8
Tool-Less Button Spacing (In.)	NA
Tool-Less Button Spacing (mm)	NA
No. of Rack Spaces	1
Surge Suppression	No
Amps	30A
Application	Distribute power to active equipment within racks and cabinets.
Length (In.)	23.25
Part Features	Scrolling power meter (on basic rack PDUs with local meters), Circuit breakers, Twist lock plug, Multiple mounting options, Mounting discs
Standards	Basic and Basic with Local Meter Rack PDUs are single-phase units with standard IEC C-13, IEC C-19, or NEMA compliant receptacles and IEC plugs or NEMA twist lock plugs.
UL Recognized	Yes
Voltage	250V
RoHS Compliancy Status	Compliant
Min. Order Qty.	1

We Welcome Your Feedback! Help Us Improve By Taking Our Short Survey

Give Feedback