

Search within category

GO

HA0A1D0CA10E1



Horizontal auto transfer switch 20 A, 120V, 10 NEMA 5-20R receptacles, two LEDs power-on indicators, and dual 10' power cord with NEMA L5-20P twist lock plug. UL and c-UL Listed. Power Feeds A and B must be Phase Synchronized. Dimensions: 1.72"H x 17.0"W x 9.0"D (44mm x 431mm x 229mm)

BUY NOW

DESIGN / INSTALL

Specs	Packaging Details	Documents	★ Add to Favorites	🛒 Add to BOM
UL Listed	Yes			
Rack PDU Type	Auto Transfer Switch Rack PDU			
Monitoring	None			
Remote Outlet Switching	No			
Mount Orientation	Horizontal			
Current Rating (Amps)	20A			
Input Voltage	120V - Single Phase			
Plug Type	(2) NEMA L5-20P			
Output Voltage	120V			
Receptacle Type	NEMA 5-20R Duplex			
Total Number of Outlets	10			
Depth (In.)	8.00			
Depth (mm)	203.2			
Height (In.)	1.72			
Height (mm)	43.7			
Width (In.)	17.12			
Width (mm)	434.8			
Tool-Less Button Spacing (In.)	None			
Tool-Less Button Spacing (mm)	None			
No. of Rack Spaces	1			
Surge Suppression	No			
Application	Single-power corded equipment.			
BMEcat - Type of Connection	Connecting cord with plug			
Cable Length	3			
Color	Black			
ETIM Number	EC002762			
Keywords	Power outlet unit			
Length (mm)	3000			
Part Features	Scrolling power meter, Switching and Dual input power sources			
Standards	UL and c-UL Listed to 60950			
Sub Brand	Auto Transfer Switch			
RoHS Compliancy Status	Compliant			

