

Search within category

GO

HA0A1M2CM10E1



Horizontal auto transfer switch 30 A, 120V, 10 NEMA 5-20R receptacles, two LEDs power-on indicators with two 20 A single pole magnetic breaker on-off switch with integral switch guard, and dual 10' power cord with NEMA L5-30P twist lock plugs. UL and c-UL Listed. Power Feeds A and B must be Phase Synchronized. Dimensions: 1.72"H x 17.0"W x 9.0"D (44mm x 431mm x 229mm)

Specs

Packaging Details

Documents

★ Add to Favorites

🛒 Add to BOM

UL Listed	Yes
Rack PDU Type	Auto Transfer Switch Rack PDU
Monitoring	None
Remote Outlet Switching	No
Mount Orientation	Horizontal
Current Rating (Amps)	30A
Input Voltage	120V - Single Phase
Plug Type	(2) NEMA L5-30P
Output Voltage	120V
Receptacle Type	NEMA 5-20R Duplex
Total Number of Outlets	10
Depth (In.)	8.00
Depth (mm)	203.2
Height (In.)	1.72
Height (mm)	43.7
Width (In.)	17.12
Width (mm)	434.8
Tool-Less Button Spacing (In.)	None
Tool-Less Button Spacing (mm)	None
No. of Rack Spaces	1
Surge Suppression	No
Application	Single-power corded equipment.
BMEcat - Type of Connection	Connecting cord with plug
Cable Length	3
Color	Black
ETIM Number	EC002762
Keywords	Power outlet unit
Length (mm)	3000
Part Features	Scrolling power meter, Switching and Dual input power sources
Standards	UL and c-UL Listed to 60950
Sub Brand	Auto Transfer Switch
RoHS Compliancy Status	Compliant

