

Search within category

GO

HA0B1E0CA1081



Horizontal auto transfer switch 20 A, 208V, 8 IEC C-13 and 2 IEC C-19 receptacles, two LEDs power-on indicators with and dual 10' power cord with NEMA 6-20P plug. UL and c-UL Listed. Power Feeds A and B must be Phase Synchronized. Dimensions: 1.72"H x 17.0"W x 9.0"D (44mm x 431mm x 229mm)

BUY NOW

DESIGN / INSTALL

Specs

Packaging Details

Documents

★ Add to Favorites

Add to BOM

UL Listed	Yes
Rack PDU Type	Auto Transfer Switch Rack PDU
Monitoring	None
Remote Outlet Switching	No
Mount Orientation	Horizontal
Current Rating (Amps)	20A
Input Voltage	208V - Single Phase
Plug Type	(2) NEMA 6-20P
Output Voltage	208V
Receptacle Type	IEC C-13 and IEC C-19
Total Number of Outlets	10
Depth (In.)	8.00
Depth (mm)	203.2
Height (In.)	1.72
Height (mm)	43.7
Width (In.)	17.12
Width (mm)	434.8
Tool-Less Button Spacing (In.)	None
Tool-Less Button Spacing (mm)	None
No. of Rack Spaces	1
Surge Suppression	No
Application	Single-power corded equipment.
BMEcat - Type of Connection	Connecting cord with plug
Cable Length	3
ETIM Number	EC002762
Keywords	Power outlet unit
Length (mm)	3000
Part Features	Scrolling power meter, Switching and Dual input power sources
Standards	UL and c-UL Listed to 60950
Sub Brand	Auto Transfer Switch
RoHS Compliancy Status	Compliant
Min. Order Qty.	1

