

Search within category

GO

HA1D2U0CA1081



Horizontal auto transfer switch 16 A, 230V, eight C-13 and two C-19 receptacles, two LEDs power-on indicators with two C-20 plugs. Complies with IEC 60950-1, EN 55022, EN 55024 and CE Marked. Power Feeds A and B must be Phase Synchronized. Dimensions: 1.72"H x 17.0"W x 8.5"D (44mm x 431mm x 216mm)

BUY NOW

DESIGN / INSTALL

Specs

Packaging Details

Documents

★ Add to Favorites

🛒 Add to BOM

CE Compliant	Yes
UL Listed	No
Rack PDU Type	Auto Transfer Switch Rack PDU
Monitoring	Local Meter
Remote Outlet Switching	No
Mount Orientation	Horizontal
Current Rating (Amps)	16A
Input Voltage	230V - Single Phase
Plug Type	(2) IEC C-20
Output Voltage	230V
Receptacle Type	IEC C-13 and IEC C-19
Total Number of Outlets	10
Depth (In.)	8.50
Depth (mm)	215.9
Height (In.)	1.72
Height (mm)	43.7
Width (In.)	17.12
Width (mm)	434.8
Tool-Less Button Spacing (In.)	None
Tool-Less Button Spacing (mm)	None
No. of Rack Spaces	1
Surge Suppression	No
Application	Single-power corded equipment.
BMEcat - Type of Connection	Connecting cord with plug
Cable Length	3
Color	Black
ETIM Number	EC002762
Keywords	Power outlet unit
Length (mm)	3000
Part Features	Scrolling power meter, Switching and Dual input power sources
Standards	UL and c-UL Listed to 60950
Sub Brand	Auto Transfer Switch

RoHS Compliancy Status		Compliant
Min. Order Qty.	1	

[LEGAL INFORMATION](#) | [PRIVACY POLICY](#) | [CONTACT US](#) | [SITE MAP](#) | [WHERE TO BUY](#) | [JOBS](#) | [UNSUBSCRIBE](#)