

Search within category

GO

HB1D2B2BM12M1



Horizontal power strip 32 A, 230V, 12 IEC C-13 receptacles, two 16 A single pole magnetic breaker / on-off switch with integral switch guard, red LED current monitor, and 3 meter power cord with a IEC 603092P+ E pin in sleeve connector. Complies with IEC 60950-1, EN 55022, EN 55024 and CE Marked. Dimensions: 1.7H x17W x.6.5D (44mm x 483mm x 165mm)

Specs	Packaging Details	Documents	★ Add to Favorites	🛒 Add to BOM
CE Compliant	Yes			
Rack PDU Type	Basic Rack PDU with Local Meter			
Monitoring	Local Meter			
Remote Outlet Switching	No			
Mount Orientation	Horizontal			
Current Rating (Amps)	32A			
Input Voltage	230V - Single Phase			
Plug Type	IEC 60309 - 6H 2P+E Blue Splashproof			
Output Voltage	230V			
Receptacle Type	IEC C-13			
Total Number of Outlets	12			
Depth (In.)	6.50			
Depth (mm)	165.1			
Height (In.)	1.72			
Height (mm)	43.7			
Width (In.)	17.00			
Width (mm)	431.8			
Tool-Less Button Spacing (In.)	NA			
Tool-Less Button Spacing (mm)	NA			
No. of Rack Spaces	1			
Surge Suppression	No			
Amps	32A			
Cable Length	3			
Length (In.)	22.50			
UL Recognized	No			
Voltage	230V			
RoHS Compliancy Status	Compliant			
Min. Order Qty.	1			