

Search within category

GO

P1N1B1L2N08ATA0



SmartZone Network-Enabled M Series Rack PDU for aggregate monitoring, horizontal 1RU, 30A, 208V single phase, (6) locking IEC C-13 and (2) locking IEC C-19 receptacles, LCD display, 10/100 RJ-45 Ethernet port with two RJ45 remote environmental ports, 10' (3m) NEMA L6-30P input cord. Dimensions: 1.7"H x 17.0"W x 8.8"D (44mm x 432mm x 225mm)

Specs	Packaging Details	Documents	★ Add to Favorites	🛒 Add to BOM
UL Listed	Yes			
Rack PDU Type	Monitored Rack PDU			
Monitoring	Aggregate Current Monitoring			
Remote Outlet Switching	No			
Mount Orientation	Horizontal			
Current Rating (Amps)	30A			
Input Voltage	208V - Single Phase			
Plug Type	NEMA L6-30P			
Output Voltage	208V			
Receptacle Type	6 IEC C-13 Locking/2 IEC C-19 Locking			
Total Number of Outlets	8			
Depth (In.)	8.84			
Depth (mm)	224.5			
Height (In.)	1.72			
Height (mm)	43.7			
Width (In.)	17.00			
Width (mm)	431.8			
Tool-Less Button Spacing (In.)	None			
Tool-Less Button Spacing (mm)	None			
No. of Rack Spaces	1			
Surge Suppression	No			
Application	Manages and distributes power to multiple rack or cabinet devices via a single power connector.			
Length (In.)	118.11			
Length (mm)	3000			
Part Features	Aggregate power monitoring, Remote power monitoring, Low profile breakers, Environmental Monitoring, Alarm thresholds, LCD digital display, Integrated locking receptacle and Customizable Configurations			
Standards	IEC C-13 and 6 IEC C-19 receptacles, IEC 60309-6H, NEMA 5-20R, NEMA 5-20P			
RoHS Compliancy Status	Compliant			
Min. Order Qty.	1			

