

Search within category

GO

PC1A1C0CA10E1



Horizontal auto transfer switch 20 A, 120V, 10 NEMA 5-20R receptacles, two LEDs power-on indicators with RJ-45 Ethernet port and red LED current monitor, and dual 10' power cord with NEMA 5-20P plug. UL and c-UL Listed. Power Feeds A and B must be Phase Synchronized. Dimensions: 1.72"H x 17.0"W x 9.0"D (44mm x 431mm x 229mm)

Specs

Packaging Details

Documents

★ Add to Favorites

Add to BOM

UL Listed	Yes
Rack PDU Type	Auto Transfer Switch Rack PDU
Monitoring	Aggregate Current Monitoring
Remote Outlet Switching	No
Mount Orientation	Horizontal
Current Rating (Amps)	20A
Input Voltage	120V - Single Phase
Plug Type	(2) NEMA 5-20P
Output Voltage	120V
Receptacle Type	NEMA 5-20R Duplex
Total Number of Outlets	10
kW	1.9
Depth (In.)	8.00
Depth (mm)	203.2
Height (In.)	1.72
Height (mm)	43.7
Width (In.)	17.12
Width (mm)	434.8
Tool-Less Button Spacing (In.)	None
Tool-Less Button Spacing (mm)	None
No. of Rack Spaces	1
Surge Suppression	No
Application	Single-power corded equipment.
BMEcat - Type of Connection	Connecting cord with plug
Cable Length	3
Color	Black
ETIM Number	EC002762
Keywords	Power outlet unit
Length (mm)	3000
Part Features	Scrolling power meter, Switching and Dual input power sources
Standards	UL and c-UL Listed to 60950
Sub Brand	Auto Transfer Switch

RoHS Compliancy Status		Compliant
Min. Order Qty.	1	

[LEGAL INFORMATION](#) | [PRIVACY POLICY](#) | [CONTACT US](#) | [SITE MAP](#) | [WHERE TO BUY](#) | [JOBS](#) | [UNSUBSCRIBE](#)