

Search within category

GO

BUY NOW

DESIGN / INSTALL



Q1N1B1F0A30AHA0

SmartZone Network-Enabled M Series Rack PDU for aggregate monitoring, vertical, 20A, 208V single phase, (24) IEC C-13 and (6) IEC C-19 receptacles, LCD display, 10/100 RJ-45 Ethernet port with two RJ45 remote environmental ports, 10' (3m) NEMA L6-20P input cord. Dimensions: 70.0"H x 2.5"W x 2.4"D (1778mm x 64mm x 60mm)

| Specs                          |                              | Packaging Details | Documents | ★ Add to Favorites | 🛒 Add to BOM |
|--------------------------------|------------------------------|-------------------|-----------|--------------------|--------------|
| CE Compliant                   | No                           |                   |           |                    |              |
| UL Listed                      | Yes                          |                   |           |                    |              |
| Rack PDU Type                  | Monitored Rack PDU           |                   |           |                    |              |
| Monitoring                     | Aggregate Current Monitoring |                   |           |                    |              |
| Remote Outlet Switching        | No                           |                   |           |                    |              |
| Mount Orientation              | Vertical                     |                   |           |                    |              |
| Current Rating (Amps)          | 20A                          |                   |           |                    |              |
| Input Voltage                  | 208V - Single Phase          |                   |           |                    |              |
| Plug Type                      | NEMA L6-20P                  |                   |           |                    |              |
| Output Voltage                 | 208V                         |                   |           |                    |              |
| Receptacle Type                | 24 IEC C-13/6 IEC C-19       |                   |           |                    |              |
| Total Number of Outlets        | 30                           |                   |           |                    |              |
| kW                             | 3.3                          |                   |           |                    |              |
| Depth (In.)                    | 2.36                         |                   |           |                    |              |
| Depth (mm)                     | 60                           |                   |           |                    |              |
| Height (In.)                   | 70                           |                   |           |                    |              |
| Height (mm)                    | 1778                         |                   |           |                    |              |
| Width (In.)                    | 2.5                          |                   |           |                    |              |
| Width (mm)                     | 63.6                         |                   |           |                    |              |
| Tool-Less Button Spacing (In.) | 64.75                        |                   |           |                    |              |
| Tool-Less Button Spacing (mm)  | 1644.6                       |                   |           |                    |              |
| No. of Rack Spaces             | 0                            |                   |           |                    |              |
| Surge Suppression              | No                           |                   |           |                    |              |
| RoHS Compliancy Status         | Compliant                    |                   |           |                    |              |
| Min. Order Qty.                | 1.0000                       |                   |           |                    |              |