Search Results

Evaluate
- FAQ's
Design a Solution
- Catalog Cut Sheet
- PDF QL0D2Q0BA241..
- Part Drawings
- PDF Switched POU ..
- Specification Sheets
- PDF 16 and 32 Am ..
How to Buy
- Bill of Material
- Favorite Products List
- Locate Distributor
Install & Maintain
- Installation Instructions
- PDF Panduit POU.
- Operation Manuals
- PDF PViQ Switche ..

Current refinements (click ☒ to remove) Search Tips

☒ **Text Search: 'QL0D2P3BN24R1'**

Your search criteria matched only one product, shown below

QL0D2P3BN24R1

• Remote switching capability for power cycling individual outlets or a group of outlets on or off to reboot equipment or power off individual outlets to stop unauthorized use
• Per outlet monitoring provides data to determine if power allocations are accurate and the efficiency metric of any server in the data center allowing individual servers to be identified as candidates for additional capacity, redeployment, or decommissioning
• Time delay sequencing avoids circuit overload due to high in -rush current at equipment start up
• Remote access to power consumption data via a web -based GUI provides global network access to real -time power information
• Integrates with Panduit ® PIM™ Software which aggregates power information through a single web based GUI
• Measure in -cabinet temperature, humidity, airflow, and dew point remotely to prevent environmental factors that can cause equipment to overheat or malfunction
• Alarm messaging capability provides user -defined alarm/messaging capabilities for specific events that exceeded thresholds
• Each outlet has a green LED for indication if the outlet is on or off for easy visual identification
• Optional remote LED display available for local monitoring, part number PVQ -RD
• Outlet Group Overload Protection allows user defined amperage threshold for a group of outlets to prevent accidental circuit breaker overload

Part Number	QL0D2P3BN24R1
RoHS Compliancy Status	Compliant
Part Description	Vertical power strip 32 A, 230/400V, WYE, 24 IEC C13 and 6 IEC C19 receptacles, RJ-45 Ethernet port with two RJ12 remote environmental ports, three 16 A double pole magnetic breaker on-off switch with integral switch guard, and 3m power cord with IEC 60309 – 3P+N+E pin in sleeve connector. Complies with IEC 60950, EN 55022, EN 55024 and CE Marked. Dimensions: 66.3"H x 2.0"W x 2.25"D (1683mm x 51mm x 58mm)
Product Type	Vertical Power Outlet Unit
Color	Black
CE Compliant	Yes
Plug Type	IEC 60309- 3P + N + E
Pricing Description	Vertical Mixed (18) C-13 & (6) C-19 Switched with per Outlet Power & Environmental Monitored 230/400V, 32A Three-Phase WYE POU
Min. Order UOM	PC
Min. Order Qty.	1
Voltage	230/400V
BOM Qty. (# of Pkgs.)	0
Add to Favorite Product List	e

Please register to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.

Copyright © 1995-2011, PANDUIT CORP. All rights reserved. | Legal Information | Privacy Policy