

Search within category

GO

BUY NOW

DESIGN / INSTALL



QL1B1L2BN24AA1

Vertical switched power strip with per outlet power and environmental monitoring, 30 A, 208V, 20 IEC C-13 and 4 IEC C-19 locking receptacles, RJ-45 Ethernet port with two RJ12 remote environmental ports, two 20 A double pole magnetic breaker/on-off switch with integral switch guard, and 10' power cord with NEMA L6-30P twist lock plug. UL and c-UL Listed.
Dimensions: 70.00"H x 2.5"W x 2.3"D Breaker Doghouse add 1.44" (87.4) to overall depth (1778mm x 64mm x 57mm)

Specs

Packaging Details

Documents

★ Add to Favorites

Add to BOM

UL Listed	Yes
Rack PDU Type	Monitored and Switched Per Outlet Rack PDU
Monitoring	Monitored Per Outlet
Remote Outlet Switching	Yes
Mount Orientation	Vertical
Current Rating (Amps)	30A
Input Voltage	208V - Single Phase
Plug Type	NEMA L6-30P
Output Voltage	208V
Receptacle Type	IEC C-13 Locking and IEC C-19 Locking
Total Number of Outlets	24
Depth (In.)	2.25
Depth (mm)	57.2
Height (In.)	70.00
Height (mm)	1778
Width (In.)	2.50
Width (mm)	63.5
Tool-Less Button Spacing (In.)	64.75
Tool-Less Button Spacing (mm)	1644.7
No. of Rack Spaces	0
Surge Suppression	No
Color	Black
Length (mm)	3000
RoHS Compliancy Status	Compliant
Min. Order Qty.	1